

530 Transmitter

Nominal Output Power:	
Inductive Mode	150 mW avg.
Conductive Mode	100 mW avg. across 2K ohms
Output Frequency:	332 kHz Continuous Wave
Battery Type:	6 Size AA Alkaline Cells
Battery Life:	50-60 hours continuous life
Operational Temperature:	-4° to + 150° F (-20° to + 50° C)
Dimensions:	13" L x 2 ¾" H x 1 ¾"D
Weight:	0.45 kg (1 lb.)

530 Receiver

Sensitivity:	
(Req'd signal at 3 ft. for 50% meter deflection)	< 1 microamp
Battery Type:	Two size 9V Alkaline Cells, Neda 1604
Battery Life:	120 hours average continuous use
Battery Check:	Automatic power-on
Operation Temperature:	-4° to + 150° F (-20° to + 50° C)
Dimensions:	30 ½"L x 2 ¾"H x 2 1/8"D
	(71cmL x 7cmH x 4.5cmD)
Weight:	0.9 kg (2 lbs.)

FEATURES

- For Locating Buried:
 - -Street Lighting
 - -Broken Tracer Wire
 - -Broken Tracer Tape
 - -Ductile or Cast Iron
 - -Blind Search
- Sleek, Lightweight Receiver Comfortable, Upright Locating
- Peak and Null Operation for Precise Locating
- Advanced Compression Circuitry Crystal Controlled for Crisp Response
- Narrow Band Antenna Eliminates Interfering Frequencies

STANDARD EQUIPMENT

Transmitter, Receiver, Conductive Attachment, Ground Rod, and Operating Manual.

ACCESSORIES

Conductive Attachment with telephone style clamps (P/N 400B246), 100 Foot Ground Lead Extension (P/N 400A132).



SERVICE CENTER, SALES AND TECHNICAL SUPPORT INFORMATION

Corporate Headquarters 3251 Olcott Street Santa Clara, CA 95054 800-446-3392 408-734-1400 Direct 408-734-1415 Fax www.metrotech.com sales@metrotech.com Metrotech Eastern U.S. Service Center 1824 Murfreesboro Road, Ste. 104 Nashville, TN 37217 800-624-6210 615-366-7323 Direct 615-360-9855 Fax nashville@metrotech.com Metrotech European Service Center Seba KMT Dr. Herbert lann St. 6 D 96148 Baunach, Germany +49 9 544 680 +49 9 544 2273 Fax Service@sebakmt.com