Models Available

		3000	2500	2000	1500	1000
Main Features	Leakage Check	•				
	Ingress Check	•	•			
	Level Check	•	•	•	•	•
	Battery Fast Charge	•	•	•	•	•
	Audio	•	•	•		
	Auto-Calibration	•	•	•		
	Enhanced Digital	•	•	•	•	•
Channel Measurement	Frequency Range	5 - 872 MHz	5 - 872 MHz	5 - 872 MHz	47 - 872 MHz	47 - 600 MHz
	Power Range - Analog	-30 to 60 dBmv	-30 to 60 dBmv	-30 to 60 dBmv	-20 to 30 dBmV	-20 to 30 dBmV
	Power Range - Digital	-23 to 67 dBmV	-23 to 67 dBmV	-23 to 67 dBmV	-13 to 37 dBmV	-13 to 37 dBmV
	Typical Accuracy at 70° F	± 0.5 dB	± 0.5 dB	± 0.5 dB	± 1.0 dB	± 1.0 dB
	Max Additional Error at 70° F	± 0.5 dB	± 0.5 dB	± 0.5 dB	± 0.5 dB	± 0.5 dB
	Typical Error from 0 to 120° F	± 1.0 dB	± 1.0 dB	± 1.0 dB	± 1.5 dB	± 1.5 dB
	Max Additional Error, 0º - 120º F	± 1.0 dB	± 1.0 dB	± 1.0 dB	± 1.0 dB	± 1.0 dB
	Digital Accuracy (Additional Errors)	± 0.5 dB	± 0.5 dB	± 0.5 dB	± 0.5 dB	± 0.5 dB
	Tuning Resolution / IF Bandwidth	125 KHz / 280 KHz	125 KHz / 280 KHz	125 KHz / 280 KHz	125 KHz / 280 KHz	125 KHz / 280 KHz
	Level Resolution	0.1 dB	0.1 dB	0.1 dB	0.1 dB	0.1 dB
Ingress	Frequency Range	5 to 872 MHz	5 to 872 MHz			
	Tuning Resolution / IF Bandwidth	250 KHz / 280 KHz	250 KHz / 280 KHz			
	Power Range from 5 to 400 MHz	-40 to 50 dBmV	-40 to 50 dBmV			
	Power Range from 400 - 872 MHz	-30 to 60 dBmV	-30 to 60 dBmV			
	Accuracy	Same as Digital Channels	Same as Digital Channels			
Leakage	Frequency Range	109 to 140 MHz				
	Tuning Resolution / IF Bandwidth	125 KHz / 280 KHz				

	Power Range	5 to 2600 uV/m using dipole at 10 ft.				
	Accuracy	Same as Analog Channels				
General	Battery: Life / Type	4 hours / 4xA Ni-MH Hi Capacity				
	Fast Charge	2 hours for 80% charge, 4 hours for 100% charge.	2 hours for 80% charge, 4 hours for 100% charge.	2 hours for 80% charge, 4 hours for 100% charge.	2 hours for 80% charge, 4 hours for 100% charge.	2 hours for 80% charge, 4 hours for 100% charge.