

Model 7510DT

Functional Specifications

| | |
|---------------------------------------|--|
| INPUT | |
| Voltage | 115/230 VAC \pm 15%, Single Phase, User selection |
| Frequency | 47 - 63 Hz |
| Fuse | 5 Amp 250V Slo-Blo |
| DIELECTRIC WITHSTAND TEST MODE | |
| Output Rating | 10 KV @ 10 mA |
| Output Adjustment | Range: 0 - 10 KV AC Resolution: 10 volt/step Accuracy: \pm (2% of setting + 10 volts) |
| HI-Limit | Range: 0.00 - 10.00 mA Resolution: 0.01 mA/step Accuracy: \pm (2% of setting + 2 counts) |
| LO-Limit | Range: 0.000 - 9.999 mA Resolution: 0.001 mA/step Accuracy: \pm (2% of setting + 2 counts) |
| Arc Detection | Range: 1 - 9 |
| Failure Detector | Audible and Visual |
| Voltage Display | Range: 0.00 - 10.00 KV Full Scale Resolution: 10 volt/step Accuracy: \pm (2% of reading + 2 counts) |
| Current Display | Auto Range Range 1: 0.000mA - 3.500mA Resolution: 0.001mA/step Range 2: 3.00 - 10.00 mA Resolution: 0.01 mA/step Accuracy: \pm (2% of reading + 2 counts) |
| AC Output Wave Form | Sine Wave, Crest Factor = 1.3 - 1.5 |
| Output Frequency | Range: 60 or 50 Hz, User Selection Accuracy: \pm 1% |

Model 7510DT cont.

| | |
|-------------------------------|---|
| Output Regulation | ± (1 % of setting + 5 volts) from no load to full load |
| Dwell Timer | Range: 0, 0.3 - 999.9 sec (0 = Constant) Resolution: 0.1 sec increments Accuracy: ± (0.1% + 0.05 sec) |
| Ramp Timer | Range: 0.1 - 999.9 sec Resolution: 0.1 sec increments Accuracy: ± (0.1% + 0.05 sec) |
| GENERAL SPECIFICATIONS | |
| PLC Remote Control | Input - Test, Reset, Recall memory # 1, # 2 and # 3 Output - Pass, Fail, Test-in-Process |
| Memory | Allows storage of up to 50 different test programs. |
| Security | Programmable password lockout capability to avoid unauthorized access to test set-up program. |
| LCD Contrast Setting | 9 ranges set by the numeric keys on the front panel. |
| Buzzer Volume Setting | 10 ranges set by the numeric key on the front panel. |
| Calibration | Software and adjustments are made through front panel. |
| Mechanical | Bench or rack mount with tilt up front feet. |
| Dimension | (W x H x D) 17 x 5.8 x 12 in. (432 x 147 x 305 mm) |
| Weight | 42 lbs (19 Kgs) |