Avionics PSD60-2R Fuel Quantity Test Set





A fuel tester that makes a powerful difference in line and hangar maintenance

The PSD60-2R performs these functions:

- Measurement of total tank capacitance, individual tank units and compensators
- Simulation of capacitance for indicator calibration
- Simulation of compensator capacitance value for dry calibration
- Measurement of the insulation resistance of tank units and aircraft harness
- Measurement of coax center conductor to shield for fault isolation
- Display of capacitance resolution to 0.00 pF for accurate individual tank unit testing (to 199.99 pF)

The PSD60-2R is an accurate, highly reliable, portable capacitance test set. Along with an aircraft specific interface, the PSD60-2R will test any AC Capacitive Fuel, Water, LOX, Engine Oil, or other AC capacitance system

- Compatible with AD 98-20-40 & AD 99-03-04 compliant aircraft (Mod 6 and above)
- Modular design for high reliability and low maintenance
- Closed box calibration using front panel controls performed annually
- Battery powered with percent of charge displayed
- · Maintenance codes displayed to aid in troubleshooting
- Distance-to-Fault (DTF) Mode determines the "length" of the wire or the approximate distance to a break in the wire or shield
- Large selection of aircraft specific interface cables readily available

GENERAL SPECIFICATIONS

MEASUREMENT RANGE

Capacitance

0.00 to 19,999 pF in 3 ranges

Resistance

 0.00Ω to 1,999 $M\Omega$ in 8 ranges

Optional range 9: 2,000 to 19,999 $M\Omega$

MEASUREMENT ACCURACY

Capacitance

 $\pm 0.1\%$ of reading or 0.05 pF, whichever is greater, from -25° to $+55^{\circ}\text{C}$

Resistance

 $\pm2\%$ of reading or 0.1 Ω , whichever is greater, from 0.00 Ω to 1,999 Ω $\pm5\%$ in optional range 9 (2,000 M Ω to 19,999 M Ω)

CAPACITANCE SIMULATOR RANGE

10 - 9,990 pF with infinite resolution

Compensator

10 - 990 pF with infinite resolution

PHYSICAL CHARACTERISTICS

Weight

12 lbs (5.4 kg)

Width

14 in (35.6 cm)

Height

6.5 in (16.5 cm)

Depth

10.6 in (26.9 cm)

Power

18 Alkaline C-size non-rechargeable batteries, internally mounted

ORDERING INFORMATION

When ordering, please include the Order Number listed below.

Ordering

Numbers Versions

693 PSD60-2R Test Set AC Capacitance Universal

Fuel Test Set

Standard Accessories

58345 Cable GND Fuel Quantity (55-7002-00)

75322 Operations Manual and CD

EXTENDED WARRANTY

84388	WPSD/203C	Extended	standard	warranty	36
	months with	scheduled c	alibration		
84389	WPSD/205C	Extended	standard	warranty	60
	months with scheduled calibration				

Aircraft specific interface cables are required and must be purchased separately. Contact Aeroflex for your application.

CHINA Beijing

Tel: [+86] (10) 6539 1166 Fax: [+86] (10) 6539 1778

CHINA Shanghai

Tel: [+86] 21 2028 3588 Fax: [+86] 21 2028 3558

CHINA Shenzhen

Tel: [+86] (755) 3301 9358 Fax: [+86] (755) 3301 9356

FRANCE

Tel: [+33] 1 60 79 96 00 Fax: [+33] 1 60 77 69 22

As we are always seeking to improve our products, the information in this document gives only a general

indication of the product capacity, performance and suitability, none of which shall form part of any contract. We reserve the right to make design changes without notice. All trademarks are acknowledged. Parent company Aeroflex, Inc. ©Aeroflex 2012.

GERMANY

Tel: [+49] 89 99641 0 Fax: [+49] 89 99641 160

HONG KONG

Tel: [+852] 2832 7988 Fax: [+852] 2834 5364

INDIA

Tel: [+91] 80 [4] 115 4501 Fax: [+91] 80 [4] 115 4502

JAPAN

Tel: [+81] (3) 3500 5591 Fax: [+81] (3) 3500 5592

Tel: [+82] (2) 3424 2719 Fax: [+82] (2) 3424 8620

SCANDINAVIA

Tel: [+45] 9614 0045 Fax: [+45] 9614 0047

SINGAPORE

Tel: [+65] 6873 0991 Fax: [+65] 6873 0992

TAIWAN

Tel: [+886] 2 2698 8058 Fax: [+886] 2 2698 8050

UK Stevenage

Tel: [+44] (0) 1438 742200 Fax: [+44] (0) 1438 727601 Freephone: 0800 282388

USA

Tel: [+1] (316) 522 4981 Fax: [+1] (316) 522 1360 Toll Free: 800 835 2352











attributes represented by these three icons: solution-minded, performance-driven and customer-focused