

OVERVIEW

PDL-1A

PDL-10A

PDL-30A

PDL-100A

PDL-100A-OEM

PDL-200A

CPDL-100A

HPDL-1A

HPDL-100A

MT-1A

MT-100A

PDM-100A

PG-1000A

SPECIFICATIONS

PG-1000A

We are offering a limited number of completely refurbished PG-1000A Pulse Generator Instruments to our customers that have purchased these units previously. All units come with a complete one year replacement warranty.

The PG-1000A Pulse Generator offers 1MHz to 1000MHz pulse generation with < 200 ps rise time for

ECL and < 750 ps rise time for TTL level output signals. Instrument control is manually via the front panel only.



PG1000A Specifications

1 MHz to 1000 MHz for ECL Frequency Range:

1 MHz to 350 MHz for TTL

+/- 0.3 digit, crystal controlled Frequency accuracy:

Frequency drift: better than +/- 1 digit Duty cycle range: 10-90% up to 50 MHz

20-80% up to 350 MHZ

30-70% up to 500 MHz

ECL Output Rise Time: < 200 ps **TTL Output Rise Time:** < 750 ps

110V AC, 90W Power Requirements: 10° C to 30° C.

Recommended Operating Temperature:

Physical Dimensions: 13 3/8" Long x 12 7/8" Wide x 5 1/4"

High.

Physical Weight: 6 kg (13.0 lbs.)

