

| | |
|--------------------------|---|
| ELECTRICAL | |
| Output | 25 Amps ac $\pm 3\%$ into any load - short circuit to 100 milliohms. Output is factory-adjustable from 10 to 30 Amps. Refer to Calibration section for details. |
| Maximum Voltage Output: | 6V |
| Pass/Fail Criterion | 100 milliohms. 100 milliohm calibration resistor supplied. (Contact factory for custom settings) |
| Ramp Time | 10 msec |
| Overshoot | none |
| Test Duration Timer | 0-20 sec. approx. |
| Duty cycle | 100 % |
| ENVIRONMENTAL | |
| Operating Temperature | 15-40°C |
| Relative Humidity Range | 0-90% non-condensing |
| GENERAL | |
| Input power requirements | See rear panel for input voltage and fuse ratings |
| Weight | 11 lbs |

Table 1-1. GF-30AC Specifications

| Non-Detachable Cordset AWG | Non-Detachable Cordset Maximum Length* |
|----------------------------|--|
| 18 | 6 feet |
| 16 | 10 feet |
| 14 | 14 feet |
| 12 | 20 feet |

Table 1-2. GF-30AC Non-Detachable Cordset Maximum Length.

*Custom configurations available for longer non-detachable cords. Contact factory.

