



Agilent 33220A 20 MHz Function/Arbitrary Waveform Generator

Data Sheet

- 20 MHz Sine and Square waveforms
- Pulse, Ramp, Triangle, Noise, and DC waveforms
- 14-bit, 50 MSa/s, 64 K-point Arbitrary waveforms
- AM, FM, PM, FSK, and PWM modulation types
- Linear & logarithmic sweeps and burst operation
- 10 mV_{pp} to 10 V_{pp} amplitude range
- Graph mode for visual verification of signal settings
- Connect via USB, GPIB and LAN

Uncompromising performance for functions and waveforms

The Agilent Technologies 33220A Function/Arbitrary Waveform Generator uses direct digital synthesis (DDS) techniques to create a stable, accurate output signal for clean, low distortion sine waves. It also gives you square waves with fast rise and fall times up to 20 MHz and linear ramp waves up to 200 kHz.

Pulse generation

The 33220A can generate variable-edge-time pulses up to 5 MHz. With variable period, pulse width, and amplitude the 33220A is ideally suited to a wide variety of applications requiring a flexible pulse signal.

Custom waveform generation

Use the 33220A to generate complex custom waveforms. With 14-bit resolution, and a sampling rate of 50 MSa/s, the 33220A gives you the flexibility to create the waveforms you need. It also lets you store up to four waveforms in nonvolatile memory.

The Agilent IntuiLink Arbitrary Waveform software allows you to easily create, edit, and download complex waveforms using the waveform editor. Or you can capture a waveform using IntuiLink for Oscilloscope and send it to the 33220A for output. To find out more about IntuiLink, visit www.agilent.com/find/intuilink.

Easy-to-use functionality

Front-panel operation of the 33220A is straightforward and user friendly. You can access all major functions with a single key or two. The knob or numeric keypad can be used to adjust frequency, amplitude, offset, and other parameters. You can



even enter voltage values directly in V_{pp}, V_{rms}, dBm, or as high and low levels. Timing parameters can be entered in Hertz (Hz) or seconds.

Internal AM, FM, PM, FSK, and PWM modulation make it easy to modulate waveforms without the need for a separate modulation source. Linear and logarithmic sweeps are also built in, with sweep rates selectable from 1 ms to 500 s. Burst mode operation allows for a user-selected number of cycles per period of time. GPIB, LAN, and USB interfaces are all standard, plus you get full programmability using SCPI commands.

External frequency reference (Option 001)

The 33220A external frequency reference lets you synchronize to an external 10 MHz clock, to another 33220A, or to an Agilent 33250A. Phase adjustments can be made from the front panel or via a computer interface, allowing precise phase calibration and adjustment.



Agilent Technologies

WAVEFORMS	
Standard	Sine, Square, Ramp, Triangle, Pulse, Noise, DC
Built-in arbitrary	Exponential rise, Exponential fall, Negative ramp, Sin(x)/x, Cardiac

WAVEFORM CHARACTERISTICS

Sine

Frequency Range	1 μ Hz to 20 MHz	
Amplitude Flatness ^{[1],[2]}	(relative to 1 kHz)	
	< 100 kHz	0.1 dB
	100 kHz to 5 MHz	0.15 dB
	5 MHz to 20 MHz	0.3 dB
Harmonic distortion ^{[2],[3]}	< 1 V _{PP}	≥ 1 V _{PP}
	DC to 20 kHz	-70 dBc
	20 kHz to 100 kHz	-65 dBc
	100 kHz to 1 MHz	-50 dBc
	1 MHz to 20 MHz	-45 dBc
		-35 dBc

Total harmonic distortion ^{[2],[3]}	
DC to 20 kHz	0.04%

Spurious (non-harmonic) ^{[2],[4]}	
DC to 1 MHz	-70 dBc
1 MHz to 20 MHz	-70 dBc + 6 dB/octave

Phase noise (10 kHz offset)	-115 dBc / Hz, typical
--------------------------------	------------------------

Square

Frequency range	1 μ Hz to 20 MHz
Rise/Fall time	< 13 ns
Overshoot	< 2%
Variable duty cycle	20% to 80% (to 10 MHz) 40% to 60% (to 20 MHz)

Asymmetry (@ 50% duty)	1% of period + 5 ns
Jitter (RMS)	1 ns + 100 ppm of period

Ramp, Triangle

Frequency range	1 μ Hz to 200 kHz
Linearity	< 0.1% of peak output
Variable Symmetry	0.0% to 100.0%

Pulse

Frequency range	500 μ Hz to 5 MHz
Pulse width (period \leq 10s)	20 ns minimum, 10 ns resolution
Variable edge time	< 13 ns to 100 ns
Overshoot	< 2%
Jitter (RMS)	300 ps + 0.1 ppm of period

Noise

Bandwidth	9 MHz typical
-----------	---------------

Arbitrary

Frequency range	1 μ Hz to 6 MHz
Waveform length	2 to 64 K points
Amplitude resolution	14 bits (including sign)
Sample rate	50 MSa/s
Min. Rise/Fall Time	35 ns typical
Linearity	< 0.1% of peak output
Settling Time	< 250 ns to 0.5% of final value
Jitter (RMS)	6 ns + 30 ppm
Non-volatile memory	four waveforms

COMMON CHARACTERISTICS

Frequency

Resolution	1 μ Hz
------------	------------

Amplitude

Range	10 mV _{PP} to 10 V _{PP} into 50 Ω 20 mV _{PP} to 20 V _{PP} into open circuit
-------	---

Accuracy ^{[1],[2]} (at 1 kHz)	$\pm 1\%$ of setting ± 1 mV _{PP}
--	---

Units	V _{PP} , V _{rms} , dBm
-------	--

Resolution	4 digits
------------	----------

DC Offset

Range (peak AC + DC)	± 5 V into 50 Ω ± 10 V into open circuit
----------------------	--

Accuracy ^{[1],[2]}	$\pm 2\%$ of offset setting $\pm 0.5\%$ of amplitude ± 2 mV
-----------------------------	--

Resolution	4 digits
------------	----------

Main Output

Impedance	50 Ω typical
-----------	---------------------

Isolation	42 Vpk maximum to earth
-----------	-------------------------

Protection	Short-circuit protected, overload automatically disables main output
------------	--

Internal Frequency Reference

Accuracy ^[5]	± 10 ppm in 90 days ± 20 ppm in 1 year
-------------------------	---

External Frequency Reference (Option 001)

Rear Panel Input	
Lock Range	10 MHz \pm 500 Hz
Level	100 mV _{PP} to 5 V _{PP}
Impedance	1 k Ω typical, AC coupled
Lock Time	< 2 seconds

Rear Panel Output	
Frequency	10 MHz
Level	632 mV _{PP} (0 dBm), typical
Impedance	50 Ω typical, AC coupled

Phase Offset	
Range	+ 360° to - 360°
Resolution	0.001°
Accuracy	20 ns

MODULATION

AM

Carrier waveforms	Sine, Square, Ramp, Arb
Source	Internal/External
Internal modulation	Sine, Square, Ramp, Triangle, Noise, Arb (2 mHz to 20 kHz)
Depth	0.0% to 120.0%

FM

Carrier waveforms	Sine, Square, Ramp, Arb
Source	Internal/External
Internal modulation	Sine, Square, Ramp, Triangle, Noise, Arb (2 mHz to 20 kHz)
Deviation	DC to 10 MHz

PM

Carrier waveforms	Sine, Square, Ramp, Arb
Source	Internal/External
Internal modulation	Sine, Square, Ramp, Triangle, Noise, Arb (2 mHz to 20 kHz)
Deviation	0.0 to 360.0 degrees

PWM

Carrier waveform	Pulse
Source	Internal/External
Internal modulation	Sine, Square, Ramp, Triangle, Noise, Arb (2 MHz to 20 kHz)
Deviation	0% to 100% of pulse width

FSK

Carrier waveforms	Sine, Square, Ramp, Arb
Source	Internal/External
Internal modulation	50% duty cycle square (2 MHz to 100 kHz)

External Modulation Input⁽⁶⁾ (for AM, FM, PM, PWM)

Voltage range	± 5 V full scale
Input impedance	5 kΩ typical
Bandwidth	DC to 20 kHz

SWEEP

Waveforms	Sine, Square, Ramp, Arb
Type	Linear or Logarithmic
Direction	Up or Down
Sweep time	1 ms to 500 s
Trigger	Single, External, or Internal
Marker	falling edge of sync signal (programmable frequency)

BURST⁽⁷⁾

Waveforms	Sine, Square, Ramp, Triangle, Pulse, Noise, Arb
Type	Counted (1 to 50,000 cycles), Infinite, Gated
Start/Stop Phase	-360° to +360°
Internal Period	1 μs to 500 s
Gate Source	External trigger
Trigger source	Single, External or Internal

TRIGGER CHARACTERISTICS

Trigger input	
Input level	TTL compatible
Slope	Rising or Falling, selectable
Pulse width	> 100 ns
Input impedance	>10 kΩ, DC coupled
Latency	< 500 ns
Jitter (rms)	6 ns (3.5 ns for pulse)
Trigger output	
Level	TTL compatible into ≥ 1 kΩ
Pulse width	> 400 ns
Output Impedance	50 Ω, typical
Maximum rate	1 MHz
Fanout	≤ 4 Agilent 33220As

PROGRAMMING TIMES (typical)

Configuration times	USB	LAN	GPIO
Function Change	111 ms	111 ms	111 ms
Frequency Change	1.5 ms	2.7 ms	1.2 ms
Amplitude Change	30 ms	30 ms	30 ms
Select User Arb	124 ms	124 ms	123 ms
Arb Download Times (binary transfer)			
	USB	LAN	GPIO
64K points	96.9 ms	191.7 ms	336.5 ms
16K points	24.5 ms	48.4 ms	80.7 ms
4K points	7.3 ms	14.6 ms	19.8 ms

GENERAL

Power Supply	CAT II 100 - 240V @ 50/60Hz (-5%, +10%) 100 - 120V @ 400Hz (±10%)
Power Consumption	50 VA max
Operating Environment	IEC 61010 Pollution Degree 2 Indoor Location
Operating Temperature	0°C to 55°C
Operating Humidity	5% to 80% RH, non-condensing
Operating Altitude	Up to 3000 meters
Storage Temperature	-30°C to 70°C
State Storage Memory	Power off state automatically saved. Four user-configurable stored states
Interface	USB, GPIO, and LAN standard
Language	SCPI - 1993, IEEE-488.2
Dimensions (W x H x D)	
Bench top	261.1mm x 103.8mm x 303.2mm
Rack mount	212.8mm x 88.3mm x 272.3mm
Weight	3.4 kg (7.5 lbs)
Safety Designed to	UL-1244, CSA 1010, EN61010
EMC Tested to	MIL-461C, EN55011, EN50082-1
Vibration and Shock	MIL-T-28800, Type III, Class 5
Acoustic Noise	30 dBA
Warm-up Time	1 hour
Warranty	1 year

Footnotes

⁽¹⁾ add 1/10th of output amplitude and offset spec per °C for operation outside the range of 18°C to 28°C

⁽²⁾ Autorange enabled

⁽³⁾ DC offset set to 0 V

⁽⁴⁾ spurious output at low amplitude is -75 dBm typical

⁽⁵⁾ add 1 ppm/°C average for operation outside the range of 18°C to 28°C

⁽⁶⁾ FSK uses trigger input (1 MHz maximum)

⁽⁷⁾ Sine and square waveforms above 6 MHz are allowed only with an "infinite" burst count

Ordering Information

Agilent 33220A

20 MHz Function/Arbitrary
Waveform Generator

Accessories included

Operating manual, service manual,
quick reference guide, IntuiLink waveform
editor software, test data, USB cable,
and power cord (see language option).

Options

Opt. 001 External timebase reference
Opt. 0B0 Delete manual
Opt. 1CM Rackmount kit
(also sold as Agilent 34190A)

Opt. A6J ANSI Z540 calibration
Opt. AB0 Taiwan: Chinese manual
Opt. AB1 Korea: Korean manual
Opt. AB2 China: Chinese manual
Opt. ABA English: English manual
Opt. ABD Germany: German manual
Opt. ABF France: French manual
Opt. ABJ Japan: Japanese manual

Other Accessories

34131A Carrying case
34161A Accessory pouch
34190A Rackmount kit



Agilent Email Updates

www.agilent.com/find/emailupdates

Get the latest information on the products and
applications you select.

Agilent T&M Software and Connectivity

Agilent's Test and Measurement software and
connectivity products, solutions and developer
network allows you to take time out of connecting
your instruments to your computer with tools
based on PC standards, so you can focus on your
tasks, not on your connections.

Visit www.agilent.com/find/connectivity
for more information.

Agilent's IO Libraries Suite ships with the
33220A to help you quickly establish an error-
free connection between your PC and instruments
—regardless of the vendor. It provides robust
instrument control and works with the software
development environment you choose.

**For additional description of Agilent's
IO Libraries Suite features and installation
requirements, please go to:**
www.agilent.com/find/iosuite-datasheet

Agilent Technologies' Test and Measurement Support, Services, and Assistance

Agilent Technologies aims to maximize the value
you receive, while minimizing your risk and
problems. We strive to ensure that you get the test
and measurement capabilities you paid for and
obtain the support you need. Our extensive support
resources and services can help you choose the
right Agilent products for your applications and
apply them successfully. Every instrument and
system we sell has a global warranty. Two
concepts underlie Agilent's overall support policy:
"Our Promise" and "Your Advantage."

Our Promise

Our Promise means your Agilent test and
measurement equipment will meet its advertised
performance and functionality. When you are
choosing new equipment, we will help you with
product information, including realistic performance
specifications and practical recommendations
from experienced test engineers. When you
receive your new Agilent equipment, we can help
verify that it works properly, and help with initial
product operation.

Your Advantage

Your Advantage means that Agilent offers a wide
range of additional expert test and measurement
services, which you can purchase according to
your unique technical and business needs. Solve
problems efficiently and gain a competitive edge
by contracting with us for calibration, extra-cost
upgrades, out-of-warranty repairs, and onsite
education and training, as well as design, system
integration, project management, and other
professional engineering services. Experienced
Agilent engineers and technicians worldwide can
help you maximize your productivity, optimize the
return on investment of your Agilent instruments
and systems, and obtain dependable measurement
accuracy for the life of those products.

**Get assistance with all your test and measurement
needs at:**

www.agilent.com/find/assist

Product specifications and descriptions in this
document subject to change without notice.

© Agilent Technologies, Inc. 2003, 2005
Printed in the USA March 14, 2005
5988-8544EN



Agilent Technologies