

Portable Digital Ohmmeter

Series 4000



The series 4000 digital ohmmeters offer true portability without any sacrifice to accuracy or functionality. These ruggedly constructed instruments are housed in a stylish plastic case with an easy to use keyboard, the measured values are displayed in large LCD panel. Many advanced measurement features are included, Long scale length 4000 count, Auto average of forward and reverse current measurement, true zero of measured value and temperature compensation (model 4001). Rechargeable batteries with automatic power off ensures the best possible battery performance.

- ❖ True 4 terminal measurement eliminates lead resistance errors
- ❖ Wide measuring range 40m Ω ...4k Ω , 10 $\mu\Omega$ resolution on lowest range
- ❖ Auto/manual range selection
- ❖ Enhanced accuracy with Auto average of forward and reverse measurements
- ❖ True Zero button
- ❖ Digital Calibration
- ❖ Automatic temperature compensation (model 4001)
- ❖ Displays Resistance and temperature -50...+800°C (model 4001)
- ❖ Rechargeable battery operation
- ❖ Auto power off to maximise battery life



IET LABS, INC.

534 Main Street, Westbury, NY 11590
Tel (516) 334-5959 (800) 899-8438 Fax (516) 334-5988 <http://www.ietlabs.com>

TECHNICAL DATA

The series 4000 portable digital ohmmeters are a practical range of instruments for low resistance measurement, ideal for use in the workshop on site or in the laboratory. Constructed in a hand portable plastic case sealed to IP54 standard the series 4000 offers many advanced features, including auto reverse of measurement current, which eliminates errors due to thermal emf. A true zero button, which will allow the measurement to be set to zero. Protection up to 415Vrms at the measurement terminals and automatic temperature compensation (model 4001).

Range selection may be either automatic or manually selected, and the rechargeable battery pack is easily and quickly replaced with a spare unit, ensuring minimum measurement down time. To further enhance the battery life an automatic power off facility is incorporated.

The measured values are displayed in a large LCD screen with LED indicator lamps to show the measurement units and open circuit lead condition.

The 4000 series are delivered ready to use with battery pack, test leads, and calibration certificate.

Range	Resolution	Typical Current	Uncertainty @20°C ±5°C, 1 year	Temperature Coefficient / °C
4kΩ	1Ω	100μA	±(0.05%Rdg + 0.02% FS)	30ppm Rdg +1 ppm FS
400Ω	100mΩ	1mA	±(0.05%Rdg + 0.02% FS)	30ppm Rdg +1 ppm FS
40Ω	10mΩ	10mA	±(0.05%Rdg + 0.02% FS)	30ppm Rdg +1 ppm FS
4Ω	1mΩ	10mA	±(0.05%Rdg + 0.03% FS)	30ppm Rdg +4 ppm FS
400mΩ	100μΩ	10mA	±(0.05%Rdg + 0.05% FS)	30ppm Rdg +25 ppm FS
40mΩ	10μΩ	100mA	±(0.05%Rdg + 0.05% FS)	30ppm Rdg +25 ppm FS

Display

15mm LCD 4000 count with automatic decimal point and polarity indication

Ranges

6 ranges, with manual or automatic range selection. LED indication of measurement units.

AVERAGE

Automatic average and display of measurement with forward and reverse current.

ZERO

Zero button to null measurement offsets

CALIBRATION

Digital Pass code protected

PROTECTION

415Vrms maximum at terminals will blow internal protection fuse

BATTERY

Removable battery pack with 4 1.5Volt rechargeable batteries. Separate battery pack docking station charger

TERMINALS

4mm safety sockets

WORKING TEMPERATURE

0...40°C rel. humidity 80% max. non condensing

Storage Temperature

-20...+50°C

SAFETY

EN61010-1 EMC-EN61326

DIMENSIONS

215 x 130 x 55mm (H W D)

MASS

0.8kg

ACCESSORIES

Supplied complete with Battery pack and external charger, measuring leads with Kelvin clips and calibration certificate

ADDITIONAL FEATURES AVAILABLE ON MODEL 4001

TEMPERATURE COMPENSATION (Model 4001)

Automatic temperature compensation with coefficients for copper, brass plus user coefficients.

TEMPERATURE MEASUREMENT

Measurement of temperature with Pt100 sensor. Measurement range -200...+850°C



IET LABS, INC.

534 Main Street, Westbury, NY 11590

Tel (516) 334-5959 (800) 899-8438 Fax (516) 334-5988 <http://www.ietlabs.com>