



# Agilent 909F

## Precision Coaxial Termination

### Data Sheet

#### DC to 18 GHz



#### Description

Agilent Technologies' 909F family of precision low reflection loads are intended for use as calibration standards.

Tantalum nitride on sapphire thin-film technology is used for exceptional long-term impedance stability. To ensure the best possible wear resistance characteristics, gold-plated beryllium copper has been used for the connector contacts.

#### Specifications

**Specifications** describe the instruments' warranted performance over the +15° to +35° C temperature range.

**Supplemental characteristics** as denoted by "typical", "nominal", or "approximate" are provided as information useful in applying the instrument, but are non-warranted performance parameters.

**Frequency Range:** dc to 18 GHz

**Impedance (nominal):** 50  $\Omega$

**Connector:**

909F, APC-7

Option 012, type-N (m)

Option 013, type-N (f)

**Reflection Coefficient (max):**

909F (typical)

dc to 5 GHz, 0.0025 (1.005 SWR)

5 to 6 GHz, 0.005 (1.01 SWR)

6 to 18 GHz, 0.07 (1.15 SWR)

Option 012 (typical)

dc to 2 GHz, 0.0035 (1.007 SWR)

2 to 3 GHz, 0.005 (1.01 SWR)

3 to 6 GHz, 0.01 (1.02 SWR)

6 to 18 GHz, 0.07 (1.15 SWR)

Option 013 (typical)

dc to 2 GHz, 0.0035 (1.007 SWR)

2 to 3 GHz, 0.005 (1.01 SWR)

3 to 6 GHz, 0.01 (1.02 SWR)

6 to 18 GHz, 0.07 (1.15 SWR)

**Power Rating:** 500 mW avg.;

100 W peak, 10  $\mu$ S/pulse

**Weight:** net—60g (2 oz);

shipping—200 g (8 oz)

#### Environmental

**Temperature:**

Operating: +15° to +35° C

Non Operating: -55° to +75° C

**Altitude:**

Operating: 15,000 ft

Non Operating: 50,000 ft

**Humidity:** Cycling 5 days,

+40° C @ 95% RH

**Vibration:** 0.015", 5-55.5 Hz,

15 min., 3 axes

**Shock:** 100 g, 1-2 ms, 3 times

3 planes

**EMC:** Radiation interference is within the requirements of MIL-STD-461, method RE02, VDE 0871, CISPR Publication 11.



Agilent Technologies



### Agilent Email Updates

[www.agilent.com/find/emailupdates](http://www.agilent.com/find/emailupdates)

Get the latest information on the products and applications you select.



### Agilent Direct

[www.agilent.com/find/agilentdirect](http://www.agilent.com/find/agilentdirect)

Quickly choose and use your test equipment solutions with confidence.



[www.agilent.com/find/open](http://www.agilent.com/find/open)

Agilent Open simplifies the process of connecting and programming test systems to help engineers design, validate and manufacture electronic products. Agilent offers open connectivity for a broad range of system-ready instruments, open industry software, PC-standard I/O and global support, which are combined to more easily integrate test system development.

### Agilent Technologies' Test and Measurement Support, Services, and Assistance

Agilent Technologies aims to maximize the value you receive, while minimizing your risk and problems. We strive to ensure that you get the test and measurement capabilities you paid for and obtain the support you need. Our extensive support resources and services can help you choose the right Agilent products for your applications and apply them successfully. Every instrument and system we sell has a global warranty. Two concepts underlie Agilent's overall support policy: "Our Promise" and "Your Advantage."

#### Our Promise

Our Promise means your Agilent test and measurement equipment will meet its advertised performance and functionality. When you are choosing new equipment, we will help you with product information, including realistic performance specifications and practical recommendations from experienced test engineers. When you receive your new Agilent equipment, we can help verify that it works properly and help with initial product operation.

#### Your Advantage

Your Advantage means that Agilent offers a wide range of additional expert test and measurement services, which you can purchase according to your unique technical and business needs. Solve problems efficiently and gain a competitive edge by contracting with us for calibration, extra-cost upgrades, out-of-warranty repairs, and onsite education and training, as well as design, system integration, project management, and other professional engineering services. Experienced Agilent engineers and technicians worldwide can help you maximize your productivity, optimize the return on investment of your Agilent instruments and systems, and obtain dependable measurement accuracy for the life of those products.

### [www.agilent.com](http://www.agilent.com)

For more information on Agilent Technologies' products, applications or services, please contact your local Agilent office. The complete list is available at:

[www.agilent.com/find/contactus](http://www.agilent.com/find/contactus)

#### Phone or Fax

##### United States:

(tel) 800 829 4444

(fax) 800 829 4433

##### Canada:

(tel) 877 894 4414

(fax) 800 746 4866

##### China:

(tel) 800 810 0189

(fax) 800 820 2816

##### Europe:

(tel) 31 20 547 2111

##### Japan:

(tel) (81) 426 56 7832

(fax) (81) 426 56 7840

##### Korea:

(tel) (080) 769 0800

(fax) (080) 769 0900

##### Latin America:

(tel) (305) 269 7500

##### Taiwan:

(tel) 0800 047 866

(fax) 0800 286 331

##### Other Asia Pacific Countries:

(tel) (65) 6375 8100

(fax) (65) 6755 0042

Email: [tm\\_ap@agilent.com](mailto:tm_ap@agilent.com)

Contacts revised: 05/05/05

Product specifications and descriptions in this document subject to change without notice.

© Agilent Technologies, Inc. 1996, 2000, 2005, 2006

Printed in USA, May 16, 2006

5091-2815E



**Agilent Technologies**