



## 39067

### Test Enclosure

Our DUT Enclosure is designed to protect the operator from electric shock during testing. By interfacing the enclosure with our Remote Safety Interlock feature the instrument's output will automatically be disabled when the enclosure door is opened.

#### Compatible Models: All Hipot instruments with Interlock

Outside dimensions: (W x D x H) 24 x 19 x 11.5 in. (610 x 483 x 293 mm)

Inside dimensions: (W x D x H) 20 x 16 x 10 in. (508 x 407 x 254 mm)

3/4" Walls

3/4" Flame Retardant Foam

1/4" Plexiglass cover



## 38814

### High Voltage Pistol Probe with Switch

High voltage test gun with dual action trigger and retractable probe tip activates the high voltage output of the instrument.



## 38081

### High Voltage Probe

## 38082

### Return Probe

Retractable high voltage and return probes for safe high voltage testing up to 5 kV. Probe tips extend/retract with a button push.



## 38539

### 2 Wire 40 Amp Ground Bond Probe

## 38538

### 4 Wire 40 Amp Ground Bond Probe

Fixed tip probes allow for easy contact with DUT ground points. Includes three different tip styles.



## CBLSR-05M

### Magnetic Hipot Return Cable

## CBLHR-05M

### Magnetic Ground Bond Return Cable

Test leads terminated in a magnetic tip allow easy connection to the DUT. Available in lengths from 5 to 15 feet.



## 35822

### Foot Switch

Ideal for use in applications where an operator needs to perform a test while using test probes.



## 39001

### Small Shipping Case

## 39087, 39088 & 39429

### Large Shipping Case

Rugged shipping cases with custom inserts to protect your Associated Research instrument from damage during shipping. Available in two sizes.



## 39077

### Test Cabinet

Test cabinet for use with any rack mountable Associated Research instrument.