

Ditchwitch Subsite 970 Transmitter



970 Transmitter

The Subsite 970T transmitter has more to offer than any other in our line: more power, more frequencies, more capabilities, and more battery life. Designed to work with our 950R and 910R receivers, it gives sophisticated users the versatility they need to locate more product more efficiently than ever before.

Key Features

- With 60% more power than its little brother, the 970T’s 5-watt output is the most productive in our line.
- Transmits all the frequencies of the 950T, plus a 200-kHz frequency for more difficult locates and more versatility.
- LCD is backlit to allow for work in low-light conditions.
- With 80 hours of battery life, this transmitter has the longest battery life in its class.
- In direct connect mode, provides additional transmitting information such as true voltage, DC resistance, and current.
- Equipped with built-in circuit protection, reverse battery protection, and live wire hookup protection for reliability.

Specifications

970 Transmitter		
Dimensions	U.S.	Metric
Length	14 in	355 mm
Height	11 in	280 mm
Width	4.2 in	107 mm
Operating Weight	7.25 lb	3.3 kg

Operations	U.S.	Metric
Operating Temperature Range	-4° F to 122° F	-20° to 50° C
Maximum power output	5 watts	5 watts
Operating Modes (some optional*): 512Hz, 1kHz, 8kHz, 29kHz, 80kHz, 200kHz*, and dual (8kHz and 29kHz)		
Timer: unit runs continuously or shuts off after running for selected hour interval (8-hour maximum)		
Batteries	8 D-cell alkaline	
Battery life	approximately 80 hours (continuous use at power level 2)	