

**236**  
**237**  
**238**

# Source-Measure Unit High Voltage Source-Measure Unit High Current Source-Measure Unit



- **Four instruments in one (voltage source, voltage measure, current source, current measure)**
- **10fA, 10pV measurement sensitivity**
- **1100V source and measure (237 only)**
- **1A source and measure (238 only)**
- **Standard and custom sweep capability including pulse**
- **1000 source/measurements per second**
- **Four quadrant source operation**
- **Internal 1000-reading memory**

## ACCESSORIES AVAILABLE

### CABLES AND CONNECTORS

237-TRX-NG	3-Slot Triax to 3-Lug Female Triax Connector
7078-TRX-3	3-Slot, Low Noise Triax Cable, 0.9m (3 ft)
7078-TRX-20	3-Slot, Low Noise Triax Cable, 6m (20 ft)

### RACKS & RACK MOUNT KITS

1938	Fixed Rack Mount Kit
1939	Slide Rack Mount Kit

### SOFTWARE

METRICS-ICS-35	IV, CV Curve Tracer Software
TestPoint™	Test Development Software

The 236, 237, and 238 Source-Measure Units (SMU) are fully programmable instruments, capable of sourcing and measuring voltage or current simultaneously. These systems are really four instruments in one: voltage source, current source, voltage measure, and current measure.

## Applications

These instruments address a wide variety of applications, including the characterization of semiconductor devices and the measurement of leakage currents or insulation resistance. They are particularly useful as source and measuring instruments in automated test equipment (ATE).

## Wide Dynamic Range

The Model 236 will source voltage from 100μV to 110V, and current from 100fA to 100mA. It can also measure voltage from 10μV to 110V and current from 10fA to 100mA. The Model 237 offers the same capabilities with a decade enhancement in voltage source and measure (1100V). In this higher voltage range, current source and measure is 10mA maximum. The Model 238 offers a decade enhancement in current source and measure (1A). In this higher current range, voltage source and measure is 15V maximum.

## Selectable Sweeps of Voltage and Current


The 236, 237, and 238 can be programmed to perform source-measurements as a function of a stepped voltage or current. Voltage and current can be swept linearly, logarithmically, or pulsed. The START, STOP, STEP method of setting sweep parameters allows operators to become proficient at using the instrument very quickly. Sweep parameters may be appended (APPEND key) to obtain more complex test sequences.

Creating custom sweeps of voltage or current is facilitated by the use of three waveform operations: CREATE, APPEND, and MODIFY. These allow the user to select waveform parameters, combine multiple waveforms, and select and change any points in a waveform previously created or appended.

## Fully-Guarded Four-Terminal Measurements

The Model 236, 237, and 238 outputs and inputs are fully guarded, and the units are configured to allow four-terminal measurements. Two-terminal measurements are also available for more standard test procedures. These outputs can be floated up to ±200V from ground.

## SMU Source Capability



## Ordering Information

<b>236</b>	<b>Source-Measure Unit</b>
<b>237</b>	<b>High Voltage Source-Measure Unit</b>
<b>238</b>	<b>High Current Source-Measure Unit</b>

**These products are available with an Extended Warranty.**

## Accessories Supplied

- 7078-TRX-10 3-Slot Low Noise Triax Cables, 3m (10 ft) (2)**
- 236-ILC-3 Interlock Cable, 3m (10 ft)**
- 237-ALG-2 Low Noise Triax Cable, 2m (6.6 ft)**

Source and measure voltage and current simultaneously

SOURCE AND MEASURE

**1.888.KEITHLEY (U.S. only)**

**www.keithley.com**

**KEITHLEY**

A GREATER MEASURE OF CONFIDENCE

# 236

# 237


# 238

## Source-Measure Unit

## High Voltage Source-Measure Unit

## High Current Source-Measure Unit

### SOURCE-DELAY-MEASURE CYCLE:



**Default Delay:** Fixed delay for instrument setting.

**User Delay:** Additional delay for device under test or system capacitance.

### MEASURE:

#### Integration Time

Fast	416 $\mu$ s	4-digit resolution
Medium	4 ms	5-digit resolution
Line Cycle	16.67 ms (60 Hz)	5-digit resolution
	20.00 ms (50 Hz)	

### EXECUTION SPEED

**MINIMUM SOURCE-DELAY-MEASURE CYCLE TIME:** 1ms.

**RESPONSE TO IEEE-488 COMMAND (as a source):** 25ms.

**MEASUREMENT RATE:** 1ms per point into internal buffer.

**CONTINUOUS MEASUREMENT SPEED (source DC value over IEEE-488 bus):** 110 readings per second.

**TRIGGER LATENCY TIME:** <2ms.

### GENERAL

**LOAD CAPACITANCE:** Stable into 20,000pF typical.

**REMOTE SENSE:** Corrects for up to 2V drop in each output lead. Maximum 1k $\Omega$  per sense lead for rated accuracy. Residual output resistance (as a voltage source) is 0.5 $\Omega$ .

**GUARD:** Output Resistance:  $\leq 12$ k $\Omega$ .

**Maximum Output Current:**  $\pm 2$ mA.

**Offset Relative to Output HI:**  $\pm 2$ mV max.

**ISOLATION (Output LO to chassis):** Typically >10<sup>10</sup> $\Omega$  in parallel with 500pF (650pF on Model 238).

**MAXIMUM COMMON MODE VOLTAGE:** 200V

**CONNECTORS:** Outputs: 3-lug triax.

**Trigger Input/Output:** BNC.

**Interlock:** 3-pin miniature DIN.

**TEMPERATURE COEFFICIENT (0°–18°C & 28°–50°C):**  $\pm(0.1 \times \text{applicable accuracy specification})/^{\circ}\text{C}$ .

#### ENVIRONMENT:

**Operating:** 0°–50°C, 70% relative humidity up to 35°C. Linearly derate 3% RH/°C, 35°–50°C.

**Storage:** –25° to 65°C.

**EMC:** Conforms to European Union Directive 89/336/EEC.

**SAFETY:** Conforms to European Union Directive 73/23/EEC (meets EN61010-1/IEC 1010).

**WARM-UP:** One hour to rated accuracy.

**COOLING:** Internal fan forced air cooling.

**POWER:** 105–125 or 210–250V AC (external switch selectable), 90–110V and 180–220V version available. 100VA max. (120VA max. on Model 238).

**DIMENSIONS, WEIGHT:** 89mm high  $\times$  435mm wide  $\times$  448mm deep (3½ in  $\times$  17¼ in  $\times$  17½ in). Net weight 9kg (19.75 lb).

### VOLTAGE

	SOURCE V			MEASURE V		
	RANGE (Max. Value)	STEP SIZE	ACCURACY (1 Year, 18°–28°C)	RESOLUTION (1 Year, 4-Digit)	5-Digit	ACCURACY (1 Year, 18°–28°C)
236, 237	$\pm 1.1000$ V	100 $\mu$ V	$\pm(0.033\% + 650 \mu\text{V})$	100 $\mu$ V	10 $\mu$ V	$\pm(0.028\% + 300 \mu\text{V})$
	$\pm 11.000$ V	1 mV	$\pm(0.033\% + 2.4 \text{ mV})$	1 mV	100 $\mu$ V	$\pm(0.025\% + 1 \text{ mV})$
	$\pm 110.00$ V	10 mV	$\pm(0.033\% + 24 \text{ mV})$	10 mV	1 mV	$\pm(0.025\% + 10 \text{ mV})$
237 Only	$\pm 1100.0$ V	100 mV	$\pm(0.04\% + 240 \text{ mV})$	100 mV	10 mV	$\pm(0.035\% + 100 \text{ mV})$
238 Only	$\pm 1.5000$ V	100 $\mu$ V	$\pm(0.033\% + 800 \mu\text{V})$	100 $\mu$ V	10 $\mu$ V	$\pm(0.028\% + 450 \mu\text{V})$
	$\pm 15.000$ V	1 mV	$\pm(0.033\% + 2.7 \text{ mV})$	1 mV	100 $\mu$ V	$\pm(0.025\% + 1 \text{ mV})$
	$\pm 110.00$ V	10 mV	$\pm(0.033\% + 24 \text{ mV})$	10 mV	1 mV	$\pm(0.025\% + 10 \text{ mV})$

**COMPLIANCE:** Bipolar current limit set with single value.

**Maximum:**  $\pm 100$ mA (except  $\pm 10$ mA on 1100V range in Model 237 and  $\pm 1$ A on 15V range in Model 238).

**Minimum:**  $\pm 1\%$  of range, except 0.5% of 1.1V range.

**Accuracy, Step Size:** Same as current source.

### NOISE (p-p):

RANGE	0.1–10Hz	DC–20MHz
110 V – 1100 V	< 3ppm of range	40 mV
11 V (15 V on 238)	< 3ppm of range	15 mV
1.1 V (1.5 V on 238)	< 10ppm of range	15 mV

**WIDEBAND NOISE:** 0.1 to 20MHz, 8mV p-p typical.

**OVERSHOOT:** <0.01% (110V step, 10mA range).

**SETTLING TIME:** <500 $\mu$ s to 0.01% (110V step, 10mA range).

**NMRR:** >60dB at 50 or 60Hz (LINE CYCLE integration time selected).

**CMRR:** >120dB at DC, 50 or 60Hz (LINE CYCLE integration time selected).

**INPUT IMPEDANCE (as a voltmeter):** >10<sup>14</sup> $\Omega$  paralleled by <20pF.

### CURRENT

	SOURCE I			MEASURE I		
	RANGE (Max. Value)	STEP SIZE	ACCURACY (1 Year, 18°–28°C)	RESOLUTION (4-Digit)	5-Digit	ACCURACY (1 Year, 18°–28°C)
All	$\pm 1.0000$ nA	100 fA	$\pm(0.3\% + 450 \text{ fA})$	100 fA	10 fA	$\pm(0.3\% + 100 \text{ fA})^1$
	$\pm 10.000$ nA	1 pA	$\pm(0.3\% + 2 \text{ pA})$	1 pA	100 fA	$\pm(0.3\% + 1 \text{ pA})$
	$\pm 100.00$ nA	10 pA	$\pm(0.21\% + 20 \text{ pA})$	10 pA	1 pA	$\pm(0.21\% + 6 \text{ pA})$
	$\pm 1.0000$ $\mu$ A	100 pA	$\pm(0.05\% + 200 \text{ pA})$	100 pA	10 pA	$\pm(0.04\% + 60 \text{ pA})$
	$\pm 10.000$ $\mu$ A	1 nA	$\pm(0.05\% + 2 \text{ nA})$	1 nA	100 pA	$\pm(0.035\% + 700 \text{ pA})$
	$\pm 100.00$ $\mu$ A	10 nA	$\pm(0.05\% + 20 \text{ nA})$	10 nA	1 nA	$\pm(0.035\% + 6 \text{ nA})$
	$\pm 1.0000$ mA	100 nA	$\pm(0.05\% + 200 \text{ nA})$	100 nA	10 nA	$\pm(0.035\% + 60 \text{ nA})$
	$\pm 10.000$ mA	1 $\mu$ A	$\pm(0.05\% + 2 \mu\text{A})$	1 $\mu$ A	100 nA	$\pm(0.038\% + 600 \text{ nA})$
	$\pm 100.00$ mA	10 $\mu$ A	$\pm(0.1\% + 20 \mu\text{A})$	10 $\mu$ A	1 $\mu$ A	$\pm(0.1\% + 6 \mu\text{A})$
	238 Only $\pm 1.0000$ A	100 $\mu$ A	$\pm(0.12\% + 700 \text{ nA})$	100 $\mu$ A	10 $\mu$ A	$\pm(0.12\% + 300 \mu\text{A})$

**COMPLIANCE:** Bipolar voltage limit set with single value.

**Maximum:**  $\pm 1100$ V (except  $\pm 110$ V in Model 238 and on 100mA range in Model 237).

**Minimum:**  $\pm 0.1\%$  of selected current range.

**Accuracy, Step Size:** Same as voltage source.

**NOISE (p-p of range):** 0.1–10Hz: <3ppm (<20ppm on 1nA and 10nA ranges and on 1A range in Model 238).

**OVERSHOOT:** <0.01% typical (10mA step,  $R_L = 10$ k $\Omega$ ).

**SETTLING TIME:** <500 $\mu$ s to 0.01% (10mA step,  $R_L = 10$ k $\Omega$ ).

**OUTPUT R, C:** >10<sup>14</sup> $\Omega$  paralleled by <20pF (on 1nA range).

<sup>1</sup> Offset specification applies for 23°C  $\pm 1^{\circ}\text{C}$  with suppression. Temperature coefficient 50fA/°C.

1.888.KEITHLEY (U.S. only)

www.keithley.com

KEITHLEY

A GREATER MEASURE OF CONFIDENCE