



[Home](#) > [Products](#) > [Source/Calibrators](#) > Model 523

Sign-Up to receive our [e-mail newsletter](#).

[Keyword Search](#)

[Print Data](#)

Model 523 - ± 4 ppm Accuracy

DC Source/Calibrator



± 4 ppm Accuracy

± 1 ppm Stability
7½ Digit Resolution

DC Voltage/Current
Source/Calibrator



EN61010-1, Safety and EN61326-1, EMC

Features

DC Voltage and Current
Relative Accuracy (90 days): ± 4 ppm
Stability: ± 1 ppm
Resolution: 7½ Digits
Wideband Noise (100kHz): $< 7\mu\text{Vrms}$
Maximum Load Current: 110mA
2 and 4-Wire Output
Auto Zero Offset Calibration (AZOC)
Automated "Covers On Calibration"
Certified to N.I.S.T.
One Year Calibration Cycle
GPIB Interface

Related Models

[Model 522](#) - ± 20 ppm to 100Vdc
> [Model 523](#) - ± 4 ppm to 100Vdc
[Model PCR100](#) - 100 ohm Precision Current Resistor

Options

PCR100: Precision 100 ohm current resistor. Used to calibrate the Models 521, 522 and 523 DC Source/Calibrators.
KH-523CAL: Calibration and Test Software Program
CAB005: Cable, 2 conductor shielded balanced line.
CAB018: Cable, multi-stacking double banana plug.
CAB023: Low thermal EMF retractable sheath banana plug patch cord set. These cables minimize thermal errors so accurate low voltage measurements can be made. Each set includes 2 test leads (one black and one red).
CAB024: Low thermal EMF spade lug patch cord for low voltage measurements. These cables minimize thermal errors so accurate low voltage measurements can be made. Each set includes 2 test leads (one black and one red).
RK-314: Rack Mount Kit permits the installation of the Model 523 into a 19" rack spacing.

Certification: A Certificate of Compliance is issued with each new instrument to certify the calibration traceable to U.S. N.I.S.T. (included).

GENERAL DESCRIPTION

The NEW Krohn-Hite Model 523 Precision DC Source is a highly stable and repeatable dc voltage source and dc current source providing N.I.S.T. traceable voltages and currents for use in production, calibration labs, QA and QC departments, design labs, or any place where an accurate voltage and current source is needed.

Using Krohn-Hite's state-of-the-art reference, the 523 provides accurate and stable voltages from $\pm 10\text{nVdc}$ to $\pm 110.99999\text{Vdc}$ to within ± 4 ppm for 90 days (± 8 ppm for 1 year), and precise currents from $\pm 10\text{nA}$ to $\pm 110.99999\text{mA}$ to within ± 8 ppm for 90 days (± 16 ppm for 1 year). It is an extremely quiet source with $< 7\mu\text{Vrms}$ of noise measured over a 10Hz to 100kHz bandwidth ($< 2\mu\text{Vrms}$ 0.1Hz to 10Hz).

The 523 features a user friendly 7½ digit display and a membrane keyboard entry of all settings. Output settings can be modified using a plus/minus delta function, multiply/divide function and curser control keys that allow placing a curser on any digit to increment or decrement its value. Output 2-wire, 4-wire and chassis grounding are accomplished with one keystroke or over the GPIB interface bus. A crowbar function places the output in a safe mode when desired. The 523 output can be set to 0 volts, allowing the output sense to maintain a true 4-wire low impedance zero output. It is also quickly forced to zero before a range change to prevent any "surprise voltages" from appearing.

An AUTO ZERO OFFSET CALIBRATION (AZOC) returns any thermally generated offsets to within specified

limits and is accessible via the front panel or over the GPIB interface bus. The unit is designed for a "Covers On Calibration" using the [KH523CAL](#) Test and Calibration Software Program (**Field Calibration License required**). With the [KH523CAL](#) program and either an HP3458 or Fluke 8508A Digital Voltmeter, unattended calibrations can be made in approximately 15 minutes.

The 523 provides for the storage of up to 31 output settings that can be recalled at any time. Internal operating temperature, serial number, last calibration date and firmware version can all be called to the display for quick access when needed. Error messages are displayed when incorrect or out-of-range entries are made.

APPLICATIONS

Krohn-Hite's NEW Model 523 is well suited for many applications where an extremely accurate and stable dc voltage or dc current is needed. At a cost much less than most sources in its class, the 523 can be a valuable asset to any company's production line, calibration lab, QA and QC department and design lab.

OUTPUT SPECIFICATIONS

The following specifications are with a constant internal operating temperature equal to 40°C ±1°C. The HP3458A NPLC is set for 100 and AUTO CAL cycle (ACAL) run. The Model 523's calibration is normally done at a room temperature of 23°C ±1°C. The internal Cal Temp is saved at the time of calibration and can be displayed with the present internal temperature using the [TEMP] key.

The 90 day and 1 year specifications are within 24 hours of a zero CQL (AZOC) cycle, and a constant internal operating temperature equal to 40°C ±1°C. The zero CAL (AZOC) cycle takes out the effect of internal DC offset drift.

(Specifications apply at an internal temperature of 40°C ±1°C, <70% relative humidity.)

Range	Res.	Relative Uncertainty ±1°C (see Note 1)		Absolute Uncertainty±1°C from calibration temperature (see Note 2)			Stability ±1°C *
		90 Days	1 Yr	24 Hours	90 Days	1 Yr	24 Hours
		----- ±(ppm output + µV or nA) -----					
DC Voltage							
111.11119mV	10nV	4 + 2	8 + 2	3 + 2	6 + 2	10 + 2	1 + 1
1.111119V	100nV	4 + 3	8 + 3	3 + 2	6 + 3	10 + 3	1 + 1
11.11119V	1µV	4 + 20	8 + 20	3 + 10	6 + 20	10 + 20	1 + 10
110.99999V	10µV	6 + 200	10 + 200	5 + 100	8 + 200	12 + 200	1 + 100
DC Current							
11.111119mA	1nA	8 + 40	16 + 40	4 + 20	10 + 40	18 + 40	2 + 20
110.99999mA **	10nA	8 + 200	16 + 200	+44 to -4, ±400	+50 to -10, ±400	+58 to -18, ±400	2 + 100
* Non-Additive							
** For values between 12mA and 110mA use graph provided with PCR100 Precision Current Resistor.							

Note 1: The RELATIVE ACCURACY specifications are to the HP3458A Digital Voltmeter used for calibration.

Note 2: The absolute accuracies and traceability to N.I.S.T. include the traceability accuracies of the calibration standard and the maintained RELATIVE accuracies of the HP3458A added to the 523 RELATIVE specifications.

Note 3: Current calibration uses an external precision 100-ohm resistor (Krohn-Hite Model PCR100) and measures the voltage using a 4-wire Kelvin connection to the resistor.

Range	Temperature Coefficient		Linearity ±1°C	Noise		Equivalent Output Z ₀ (ohms)
	18°C - 28°C	0°C - 40°C		0.1Hz - 10Hz	10Hz - 100kHz	
	±(ppm output + μV or nA)/°C			p-p	rms	
DC Voltage						
111.11119mV	1 + 0.2	2 + 0.2	1 + 1	2μV	7μV	0.1μ
1.1111119V	1 + 0.5	2 + 0.5	1 + 1	2μV	7μV	1μ
11.111119V	1 + 1	2 + 1	1 + 10	4μV	15μV	10μ
110.99999V	2 + 10	4 + 10	1 + 100	40μV	100μV	100μ
DC Current						
11.111119mA	2 + 5	4 + 5	1 + 20	20nA	150nA	10G
110.99999mA	2 + 10	4 + 10	1 + 100	200nA	300nA	1G
Temperature coefficient is best straight line fit method.						

Settling Time: <10ms.

Line Regulation: $<\pm 0.1$ ppm change for a 10% change from normal line voltage, typically no measurable change.

Load Regulation 4-Wire operation: $<\pm 0.1$ ppm change from no load to 100mA full load, typically no measurable change. Measurements must be made at sense lead connection point to the load.

Compliance Voltage Effect On Current Output: <10 nA change for a 100V change in compliance voltage for output currents <11.11112 mA, equivalent to >10 Gig-ohm output impedance; <100 nA change for a 100V change in compliance voltage for output currents ≥ 11.11112 mA, equivalent to >1 Gig-ohm output impedance.

Compliance Voltage Limit: Settable in 1V steps from 1V to 110V. Compliance limits approximately 15% ± 0.25 V above the setting.

Warm-Up Time from a Cold Start: 1 Hour to within 5ppm of final value. 4 Hours to rated accuracy and final value.

Maximum Output Current: ± 110 mA. Output protected from damage with a current limiter. Output may be shorted to ground indefinitely.

Calibration: The Model 523 is specified with a 1-year calibration cycle. An AUTO ZERO OFFSET CALIBRATION (AZOC) is provided that returns any thermally generated offset to within specified limits, and can be accessed via front panel controls or over the GPIB interface bus. The Model 523 is designed for a "Covers On" calibration using the [KH523CAL](#) Test and Calibration Software Program (license required). The [KH523CAL](#) software, together with an HP3458A or Fluke 8508A Digital Voltmeter, allows virtually unattended calibration to be performed in approximately 15 minutes. The calibration date and internal temperature is stored in memory and can be called to the display or over the GPIB interface bus.

Calibration Temperature Limits ("Covers-On Calibration"): Internal temperature (T Cal), $40^{\circ}\text{C} \pm 1^{\circ}\text{C}$; Ambient temperature (T Amb), 0°C to 30°C .

Protection: Voltage mode, short-circuit and over-load protected. Current mode, open circuit protected. Indication by display message. Automatic recovery.

GPIB PROGRAMMING

Switching Time: Typically 300ms.

Subsets: SH1, AH1, T6, SR1, RL1, PP1, DC1, DT1, CO, E1.

Line Termination: The GPIB OEI signal is always sent with the last character on a line.

Talker Function: Allows interrogation of the Model 523 by a controller.

TERMINALS

Output Terminals are mounted on both the front and rear panels. Only one set of terminals may be used at a time. Both terminal sets are configured for remote sensing of the output as follows:

High Output and High Sense
Low Output and Low Sense
Case Ground.

GENERAL

Display: LCD, 7.5 digits. Displays output settings and other pertinent information.

Isolation: Power transformer-to-analog output, control logic-to-analog output, optically isolated.

SAFETY

The Model 523 is designed to meet the requirements of the following standards of safety for electrical equipment for measurement, control and laboratory use: IEC61010-1, EN61010-1

ELECTROMAGNETIC COMPATIBILITY

Emissions and Immunity: EN61326-1, EMC, 61000-4-2; ESD, 61000-4-3; Radiated Immunity, 61000-4-4; EFT, 61000-4-5; Surge, 61000-4-6; Conducted Immunity, 61000-4-8; Magnetic Immunity, 61000-4-11; Voltage Interruption EN61010-1.

CE Compliant for Class B Equipment.

MECHANICAL

Power Requirements: Selectable 105-130 or 210-260 volts ac, single phase, 50Hz to 60Hz, 60 watts

Dimensions and Weights: 3.5" (9cm) high, 14" (36cm) wide, 12.5" (32.13cm) deep;
12 lbs (5.4kg) net, 14 lbs (6.3kg) shipping.

Operating Temperature Range: 0°C to 50°C .

OPTIONS

PCR100: 100 Ohm Precision Current Resistor

RK-314: Rack Mount Kit permits the installation of the Model 523 into a 19" rack spacing.

KH523CAL: Calibration and Test License - License to unlock the 523 for calibration with KH523CAL Calibration Software.

CAB005: Cable, 2 conductor shielded balanced line.



CAB018: Cable: multi-stacking double banana plug.



CAB023: The CAB023 is a low thermal EMF retractable sheath banana plug patch cord set. These low thermal cables minimize thermal errors so accurate low voltage measurements can be made. Each set includes 2 test leads (one black and one red).



CAB024: The CAB024 is a low thermal EMF spade lug patch cord set for low voltage measurements. These low thermal cables minimize thermal errors so accurate low voltage measurements can be made. Each set includes 2 test leads (one black and one red).



ACCESSORIES
3 terminal line cord.
Operating manual.

Specifications are subject to change without notice.

Copyright © August 01, 2008 Krohn-Hite Corporation. All rights reserved.



15 Jonathan Drive, Unit 4, Brockton, MA 02301-5566 U.S.A.
Tel: (508) 580-1660; Fax: (508) 583-8989; sales@krohn-hite.com