

# 810Dx Pipe and Cable Locator

## Technical Data

### Features:

- Single High Frequency – 83 kHz, Jumps Insulators and Gaskets
- Ergonomic Receiver is Comfortable to Carry
- Distance Sensitive Left / Right Guidance™
- Simultaneous Peak & Null Display™
- Real Time Continuous Gain Adjustment™
- Battery Saving Constant Current Transmitter
- Single Push-Button Depth
- Compatible with Model 810



### Standard Equipment:

Transmitter, Receiver, Conductive Attachments, Earth/Ground Rod, Hard Carrying Case, Operation Manual.

### Optional Equipment:

MetroClamp™ Inductive Couplers: 4290 (2"), 4920, 4490 (4"), 4890 (8"), Sondes: SON830 (Small), SONH83K (Large), Training CD.

### 810Dx Receiver

Receiving Frequency	83.0775 kHz
Depth Readout Accuracy	+/-5% + 2" under normal conditions (0-10 ft)
Depth Readout Range	To 20 ft (600 cm)
Left right indication	Distance Sensitive Left/Right Guidance™
Automatic gain	Real Time Continuous Gain Control™
Battery type	8 AA Alkaline
Battery life	80 hrs continuous
Operating temperature	-4°F to +122°F (-20°C to +50°C)
Dimensions	28.7" L x 8.63" W x 12.25" H (72.9 x 21.9 x 31.1 cm)
Weight	3.9 lbs (1.8 kg)
Regulatory Compliance	FCC, CE
Environmental	IP54

### 810Dx Transmitter

Output frequency	83.0775kHz Crystal Controlled
Output Power	1 Watt
Battery Type	6 NEDA 13F Alkaline D cells or NiMH rechargeable
Battery Life	Alkaline 100 hours Continuous use NiMH 50 hours Continuous use
Operating Temperature	-4°F to +122°F (-20°C to +50°C)
Dimensions	8.5" L x 4.63" W x 7.0" H (21.6 x 11.8 x 17.8 cm)
Weight	w/D cell 5.16 lbs (2.34 kg) w/NiMH 5.48 lbs (2.48)
Regulatory Compliance	FCC, CE
Environmental	IP54

### Service Center, Ordering, and Technical Support Information

#### Corporate Headquarters

**Western United States Service Center**  
488 Tasman Dr., Sunnyvale, CA 94089  
Sales Tel: 1.800.446.3392 (U.S./Canada)  
Service Tel: 1.800.638.7682  
Tel: +1.408.734.1400 (International)  
Fax: +1.408.734.1415  
[www.metrotech.com](http://www.metrotech.com); [sales@metrotech.com](mailto:sales@metrotech.com)

#### Northeastern Sales Office

89 S Commerce Way, Suite 940  
Bethlehem, PA 18071  
Tel: +1.866.644.8537  
Fax: +1.610.861.1996  
[sales@metrotech.com](mailto:sales@metrotech.com)

#### Metrotech Eastern United States Service Center

1824 Murfreesboro Rd., #104  
Nashville, TN 37217  
Tel: 1.800.624.6210 (U.S./Canada)  
Tel: +615.366.7323 (International)  
Fax: +1.615.360.9855  
[nashville@metrotech.com](mailto:nashville@metrotech.com)

#### Metrotech European Service Center

SebaKMT  
Dr.-Herbert-Iann-Str. 6, D-96148  
Baunach, Germany  
Tel: +49.9544.680  
Fax: +49.9544.2273

**Warranty:** One year provided on parts and labor

Specifications subject to change without notice. Copyright 2004

Distance Sensitive Left / Right Guidance, Simultaneous Peak & Null Display,

Real Time Continuous Gain Adjustment, MetroClamp are Trademarks of Metrotech Corp.



ISO 9001 Certified