

Guardian

USES:

- Production and Compliance Testing of Appliances, Instruments and Information Technology Equipment in Accordance with UL, CSA, IEC, TUV and Other Standards such as EN60335, UL60950, EN61010 and CSA C22.2 No. 1010.1
- Transformer Electrical Safety Testing
- Electric Motor Safety Testing
- Power Supply Safety Testing
- Verification of the Ground Connection on Products with a Three Prong Power Cord

FEATURES:

- Twin Port - Simultaneous Hipot & GB
- Built-in 20A Hipot/Line Leakage Scanner
- Output Voltage to 5kV AC and 6kV DC
- Ground Bond Testing to 30A AC (to 40A with Optional Transformer)
- Insulation Resistance Measurements from 100k Ω to 50G Ω
- Earth, Enclosure & Patient Line Leakage Current Measurements to 9.999mA
- Open/Short Circuit Detection Mode
- Pause Mode with Message Capability
- Continuous Leakage Current Monitoring
- Programmable Trip Current to 40mA AC and 12mA DC
- Programmable Ramp, Dwell & Test Times
- Storage of 100 Test Setups, 50 Steps Each
- Front Panel Lockout via Password
- Standard RS-232 & Remote I/O Interfaces
- Optional IEEE-488, Printer Interfaces
- Optional CaptivATE Automation Software for G6100 Plus

6100 Plus Safety Analyzer

for Electronics Production & Compliance Testing

Introduction

The Guardian 6100 Plus is the industry's first production safety analyzer with simultaneous Hipot and Ground Bond capability providing a dramatic savings in test time. Six instruments in one, the G6100 Plus provides AC Hipot, DC Hipot, Insulation Resistance, Leakage Current/ Functional Run, Ground Bond and Open/ Short measurements from a single test connection. Versatile and packed with features, the G6100 Plus is a cost effective solution for the full spectrum of electrical safety compliance testing.

Description

Twin Port Technology: This patented feature allows for simultaneous Ground Bond and Hipot Testing. Decrease test time and increase device through-put.

Leakage Current: With 20A input current capability, Leakage Current can be measured from 0.1 μ A to 9.999mA. Perform Functional Run Tests while monitoring the Voltage, Current or Power plus perform Earth, Enclosure and Patient leakage testing in 8 possible modes including Normal, Reverse Line, Single Fault Normal and Single Fault Reverse.

Ground Bond: With test current from 1A to 30A in 0.1A steps and programmable current limits, test time, frequency and open circuit no load voltage, the G6100 Plus provides full GB testing capability. A 40Amp GB option is also available.

AC Hipot: AC dielectric testing over the voltage range from 50V to 5000VAC RMS. The maximum leakage current of 40mA RMS is ideal for testing devices with high leakage currents such as power supplies which have large filter or "Y" capacitors for noise reduction.

DC Hipot: DC dielectric testing from 50V to 6000VDC with a resolution of 1V. Leakage current can be continuously monitored from 0.1 μ A to 12mA DC.

Insulation Resistance: The G6100 Plus is capable of measuring IR from 100k to 50G Ω with test voltage from 50V to 1000VDC in 1V steps.

Open/ Short Circuit Detection Mode: Avoid false pass results by checking for Open and Short connections and ensure that the DUT is properly connected not shorted.

Optional Scanners: Increase the number of test channels for multi-point or multi-device testing by adding an external scanner to the G6100 Plus. Add up to 8HV channels or a combination of HV and GB channels with just one external scanner.

Standard Interfaces: The Remote I/O and RS-232 interfaces provide remote control and serial data collection capability for automated applications.

For more detailed specifications, visit

www.quadtech.com

1-800-253-1230

Fax 1-978-461-4295

Intl. 1-978-461-2100



HIPOT TESTERS LCR METERS MEGOHMMETERS MILLIOHMMETERS CABLE TESTERS

Guardian 6100 Plus

AC Output Voltage:	Range: 50V to 5000V AC, 1V resolution Freq: 50-600 Hz, programmable in 1Hz steps Waveform: Sinusoidal Regulation: <(1% of setting +5V) at Rated Load
Voltage Display:	Accuracy: $\pm(1\%$ of reading + 5V) Resolution: 1Volt
AC Current Display:	Total current, Range: 0.001 to 40mA AC Resolution: 1 or 10 μ A steps Accuracy: $\pm(1\%$ of reading + 5cnt)
High/Low Limit Test:	1 μ A to 40mA AC Low limit can be turned OFF
Arc Detection:	Programmable 1-20mA, Pulse Width 40 μ , 20 μ , 10 μ or 4 μ sec
DC Output Voltage:	Range: 50V to 6000V DC, 1V resolution Regulation: <(1% of setting +5V) at Rated Load
Voltage Display:	Accuracy: $\pm(1\%$ of reading + 5V) Resolution: 1Volt
DC Current Display:	Range: 0.1 μ to 12mA DC Resolution: 0.1, 1 or 10 μ A steps Accuracy: $\pm(1\%$ of reading + 5cnt)
High/Low Limit Test:	0.0001mA to 12mA DC Low limit can be turned OFF
Arc Detection:	Programmable 1-10mA Pulse Width 40 μ , 20 μ , 10 μ or 4 μ sec
Insulation Resistance:	Range: 100k Ω - 50G Ω Accuracy: $\pm 5\%$ to $\pm 15\%$ depending upon voltage and resistance
Voltage Range:	50V to 1000V DC
Voltage Accuracy:	$\pm(1\%$ of setting + 5V)
High/Low Limit Test:	100k Ω - 50G Ω Low limit can be turned OFF
Ground Bond:	
Output Current:	Range: 1.0 to 30.0A AC, setting 0.1A/step; *40A Accuracy: $\pm(1\%$ of setting + 0.3A)
Frequency:	50 or 60Hz Selectable
No Load Voltage:	6 to 15 V Programmable
Resistance:	Range: 0.1m Ω -510.0m Ω , 4 digits; Resol: 1m Ω Accuracy: $\pm(1\%$ of reading + 3 counts)
High Limit:	0.1m Ω to 510m Ω
Start Wait:	0.1 - 99.9sec, OFF
Leakage Current:	
Input Voltage:	Range: 0V to 300V
Line Voltage Meter:	0 - 300V AC, $\pm(1\%$ of reading + 6cnts)
Line Current Meter:	0 - 20A, $\pm(1.5\%$ of reading + 0.1A)
Power:	0 - 4400VA
High/Low Limits:	Programmable for Voltage, Current, Power

Current Display:	Range 0.0001-0.59mA 0.6 - 9.999mA	Res. 0.0002mA 0.003mA	Accuracy $\pm(2\% + 5\text{cnts})$ $\pm(2\% + 5\text{cnts})$
Current Trip Limits:	0.1 μ A to 9.999mA, 1 μ A Resolution (Range Dep.) 0.1 μ A to 6.000mA for UL544NP		
Measuring Circuit:	5 Human Body Models IAW UL544 NP, UL544P, UL1563, UL2601-1, IEC60601-1, IEC 950, UL1950, UL3101 Standards		
Measurement Modes:	Normal, Reverse, Single Fault with Ground ON/OFF, Earth Line Leakage, Patient Line Leakage and Patient Auxiliary Leakage.		
Max. DUT Current:	20A		

Common Features:

Open/Short Circuit Mode:	Check for Open & Short against a standard capacitance value (Cs); <100V, 600Hz
Offset Function:	0 to 100m Ω offset, user selectable
Test Time:	Ramp: 0.3 to 999s ($\pm 20\text{ms}$), AC/DC/IR Dwell: 0 to 999s ($\pm 20\text{ms}$), DC only Start Wait: 0.1 to 99.9s ($\pm 20\text{ms}$), GB only Test: 0.3 to 999s ($\pm 20\text{ms}$) & Continuous
Remote Control:	Inputs: Start, Stop Characteristics: Optically Isolated, Low, Pulse Width >1ms. Outputs: Pass/Fail/Under Test Characteristics: Dry Contact relay Electrical Characteristics: 120V 100mA max. Logic: Closed if True Connector: Terminal Strip and 9 pin D Series
Test Setups:	100 Test Setups with 50 Steps each, 13 character Alpha-Numeric Label
Connectors:	Front and Rear 4- terminal connection
Display:	320 x 240 enhanced LCD, status indicators
Front Panel Lockout:	Key Lock w/ Password; Fail Lock w/ Password
Safety Features:	Fast Cutoff (<0.4ms) & Fast Discharge (0.2s) Adjustable Discharge: .05-5.1kV DC
Miscellaneous:	Fail Retest; Continue on Fail PAUSE Mode: Program pause between steps
Indication:	Pass/Fail lights, audible sound; Remote, Lock, Offset & Error status indicators
Standard Interfaces:	RS-232, Remote I/O
Optional Interfaces:	IEEE-488, Printer
Dimensions:	(w x h x d): 17x5.25x18.5in (430x133x470mm)
Weight:	53 lbs (24kg) - Net, 60 lbs (27kg) Shipping
Environmental:	Operating: 0 to + 40° C; Humidity: <75% Storage: - 20 to + 70° C
Power:	• 90 - 130V AC • 50 or 60Hz • 200 - 250V AC • 800W max

Ordering Information

*GB to 40A with optional transformer

Guardian 6100 Plus Safety Analyzer		Optional Accessories	G14	Power Entry Adapter
Includes:		N/A	G16	International Power Strip
150799	Instruction Manual	5000-01	G24	Scanner Cable (5000 scanners)
S02	HV Lead Set, 1m	5000-02	G25	Corded Product Adapter (240V)
G15	Ground Continuity Lead Set		G31	Isolation Transformer, 500VA
G30	Corded Product Adapter	5000-03	G32	Isolation Transformer, 1000VA
G33	Power Entry Adapter	5000-04	G38	Printer Interface (replaces IEEE)
4200-0300	AC Power Cable	S04	G39	IEEE-488 Interface
520157	8A 250V Power Line Fuse	S05	G43	Rack Mount Kit
520053	4A 250V Power Line Fuse	S08	G44	Barcode Scanner
520124	20A 250V Power Line Fuse:	S09	G45	40A Ground Bond Transformer
	Scanner	S10	630157	RS232, 9-pin (M-F), 10' length
N/A	Calibration Cert. Traceable to NIST	G13		

For more detailed specifications, visit www.quadtech.com • For more information about special purchase, rent & lease options, call:

1-800-253-1230 • Fax 1-978-461-4295 • Intl. 1-978-461-2100
5 Clock Tower Place, 210 East, Maynard, MA 01754



P/N: 030147/A1