

Serving Your Video Needs Since 1955



VSB Player Signal Source



Designed To Give You Full Control Of Your Video Content For Both Analog and Digital Video Receivers In A Variety Of Applications Including In-Store Demonstrations, Special Events, and Product Testing.

The HDTV996A provides you with:

An ATSC 8 VSB and NTSC modulated outputs for use on both analog and digital receivers

TTL and LVDS parallel Transport Stream Output

Supports all ATSC formats including 720P and 1080I for true high definition signals

Multiple Input Path For Data Stream including:

- TTL or LVDS Parallel
- On-Board Network Interface
- CD/DVD Drive Input
- Optional 8 VSB Demod Card

Local or Remote Customization Of Your Entire Playlist

Easy-To-Use Front Panel Operation Enables Everyone To Operate The Unit

HDTV996A Specifications

System: Display:

board

Size:

HWD

Weight:

General:

Operating System:

Network Interface:

Internal Drive Bays:

Operating Temperature:

ATSC Transport Stream Output:

Input Source: TTL or LVDS (selectable)

Data Bit Rate: 19.392659 MB/sec

Output: TTL and LVDS (simultaneous)

RF Modulated Outputs:

ATSC Output Frequency: UHF 14- 21 NTSC Output Frequency: VHF 3-13 Frequency Accuracy: +/- 10 kHz

Modulation Type: 8 level VSB trellis for ATSC

Terr.

Output impedance: 75 Ohm

Output Power Level: +3 to +6 dBmV

In-Band SNR(ATSCchannel): 30 dB with equalization

Program Storage:

Total Play Time: 500-plus minutes(total)

Max. number o programs: 255

Data Compatibility: All formats in ATSC standard Hard Disk Drive: 80 Gbyte-7200 RPM(standard)

Product Options

Program Material- Custom loaded programming(material supplied by purchaser or licensed through Sencore)

Demodulation Card- Allows you to receive off-air 8 VSB signals and record content directly to hard-drive of the HDTV996A.

Call your representative for more details

SENCORE

The Leader For All Your Video Needs

WWW.SENCORE.COM



4-lines by 20 characters

Microsoft Windows 2000

Integrated on ATX mother-

17.5 cm X 35 cm X 38 CM

prov. for 2nd HDD

15 to 35 degrees C

20 lbs.

Call Us Today At 1-800-SENCORE (736-2673)