

1.3 Power Supply Features (continued)

- External indicator signals for remote monitoring of OVP status, local/remote programming status, thermal shutdown, and output voltage and current.
- Optional IEEE-488 interface for complete remote programming and readback capability.

1.4 Specifications

1.4.1 Electrical Specifications¹

MODELS	8-125	20-50	33-33	40-25	60-18	80-13	150-7	300-3.5	600-1.7
Output Ratings:									
Output Voltage	0-8V	0-20V	0-33V	0-40V	0-60V	0-80V	0-150V	0-300V	0-600V
Output Current	0-125A	0-50A	0-33A	0-25A	0-18A	0-13A	0-7A	0-3.5A	0-1.7A
Output Power	1000W	1000W	1089W	1000W	1080W	1040W	1050W	1050W	1020W
Line Regulation ² :									
Voltage	8mV	20mV	33mV	40mV	60mV	80mV	150mV	300mV	600mV
Current	125mA	50mA	33mA	25mA	18mA	13mA	7mA	3.5mA	1.7mA
Load Regulation ³ :									
Voltage	8mV	20mV	33mV	40mV	60mV	80mV	150mV	300mV	600mV
Current	125mA	50mA	33mA	25mA	18mA	13mA	7mA	3.5mA	1.7mA
Meter Accuracy:									
Voltage	0.09V	0.3V	0.43V	0.5V	0.7V	0.9V	1.6V	4.0V	7.0V
Current	1.35A	0.6A	0.43A	0.35A	0.28A	0.23A	0.08A	0.045A	0.018A
OVP Adjustment Range	0.4-8.8V	1.0-22V	1.65-36.3V	2-44V	3-66V	4-88V	7.5-165V	15-330V	30-660V
Output Noise and Ripple (V)									
rms	10mV	10mV	10mV	10mV	20mV	20mV	30mV	40mV	100mV
p-p	100mV ⁴	100mV ⁴	100mV ⁴	100mV ⁴	100mV	100mV	200mV	200mV	500mV
(20Hz-20MHz)									

¹ Specifications are warranted over a temperature range of 0-50°C with default local sensing. From 50-70°C, derate output 2% per °C.

² For input voltage variation over the AC input voltage range, with constant rated load

³ For 0-100% load variation, with constant nominal line voltage

⁴ Typical P-P noise and ripple is 50mV

AC Input: 200-250Vac at 10Arms or 100-130Vac at 20Arms, 47-63Hz

Maximum Voltage Differential from output to safety ground: 600Vdc

Additional Characteristics

MODELS	8-125	20-50	33-33	40-25	60-18	80-13	150-7	300-3.5	600-1.7
Stability ¹ :									
Voltage	4mV	10mV	16.5mV	20mV	30mV	40mV	75mV	150mV	300mV
Current	62.5mA	25mA	16.5mA	12.5mA	9mA	6.5mA	3.5mA	1.75mA	0.85mA
Temperature Coefficient ² :									
Voltage	1.6mV	4mV	6.6mV	8mV	12mV	16mV	30mV	60mV	120mV
Current	37.5mA	15mA	9.9mA	7.5mA	5.4mA	3.9mA	2.1mA	1.05mA	0.51mA
Maximum Remote Sense Line Drop Compensation /line	0.5V	1V	1V	1V	1V	1V	1V	1V	1V

¹ Maximum drift over 8 hours with constant line, load, and temperature, after 90 minute warmup

² Change in output per °C change in ambient temperature, with constant line and load

Additional Characteristics (continued)**Storage Temperature Range:** -55 to +85°C**Humidity Range:** 0 to 80% Non-condensing**Time Delay from power on until output stable:** 2 seconds maximum**Voltage Mode Transient Response Time:** 1mS recovery to 1% band for 30% step load change from 70% to 100% or 100% to 70%**Remote Start/Stop and Interlock:** TTL compatible input, Contact Closure, 12-250Vac or 12-130Vdc**Switching Frequency:** Nominal 100kHz, 200kHz output ripple (>80V models = 80kHz, 160 kHz output ripple.**Analog Programming Linearity:** Typical error is less than 0.5% setting. Maximum error is 1% of rated output.**Agency Approvals:** CSA, UL**Remote Analog Programming (Full Scale Input)**

Scales are selectable via an internally-mounted switch.

PARAMETER	RESISTANCE	VOLTAGE	CURRENT
Voltage	5k Ω	5V, 10V	1mA
Current	5k Ω	0.1V, 5V, 10V	1mA
OVP	5k Ω	5V, 10V	1mA

1.4.2 Mechanical Specifications

	HEIGHT	WIDTH	DEPTH	WEIGHT
Single Unit	44mm (1.75in)	482.6mm (19in)	508mm (20in)	8.2kg (18lbs)

Output Connector

- Models DCS 8-125 through DCS 80-13**

Connector type: Nickel plated copper bus bars.**Approximate dimensions:** 1.365" x 0.8" x 0.125"**Distance between positive and negative bus bar centers:** 2.2"**Load wiring mounting holes:** Two 0.257" diameter holes on 0.5" centers (1/4" hardware)
Two 0.191" diameter holes on 0.4" centers (#10 hardware)

- Models DCS 150-7 through DCS 600-1.7**

Connector type: Six pin Amp Universal Mate-N-Lok connector**Chassis mounted parts:** Housing: Amp part number 1-480705-0

Pins: Amp part number 350547-1

Mating connector parts: Housing: Amp part number 1-480704-0

Socket pins: Amp part number 350550-1

Note: Eight Socket pins and one mating connector housing are supplied in a ziplock bag packaged with each 150V through 600V unit.