





Key Features

- Cost-effective timing source for telecom/metrology test/ measurement applications
 - SDH/SONET/PDH, Jitter/Wander measurement source
 - Compact, robust and lightweight, easy handling
 - Cesium reference input with auto-calibration feature
 - Accuracy 1 × 10⁻¹² with GPS reference
 - Outputs: E1/T1, 2048/1544 kHz
- With and without GPS input available

Product description

The TSR-37 is a low-cost portable timing reference based on a superior rubidium oscillator technology for universal use in telecom and metrology as well as in test and measurement applications.

It provides a number of coherent output signals

- Sine wave 10 MHz and 5 MHz
- · 2048 kHz and 1544 kHz balanced and unbalanced
- E1 2048 kbps balanced and unbalanced
- T1 1544 kbps balanced and unbalanced

with excellent stability and aging performance specially designed for both stationary applications and mobile operations.

All reliable output signals are based on the highly accurate and stable rubidium oscillator inside. The rubidium's fast warm up eliminates the need of bulky backup batteries.

The TSR-37 can be locked to an external primary source such as a cesium standard for automatic frequency calibration of the rubidium oscillator.

The unit is available in two versions:

- TSR-37
- TSR-37 GPS

The GPS version supports a high performance GPS functionality to control the rubidium oscillator. Nearly cesium quality can be achieved in GPS controlled operation by using a standard L1 GPS installation. Additionally GPS can be used as an alternative calibration input, without using an expensive primary reference source.

Applications

Telecom

The TSR-37 is a powerful reference source to quickly measure and test the synchronization quality of PDH/SDH/SONET digital networks. MTIE and TDEV measurements for up to 1000 seconds can be easily performed without a GPS reference. Coupled with the external GPS antenna, the range of observation time can be largely extended to meet specific requirements.

Metrology

Standard 5 MHz and 10 MHz sine wave outputs of the TSR-37 are typically provided for metrology and calibration laboratory equipment such as

- Universal counter
- Spectrum analyzer
- Synthesized signal generator



Typical application

Operation with other JDSU products

The TSR-37 provides the reference clock for wander analysis using the ANT-20, ANT-10G Advanced Network Tester.





Functional features of the product

Automatic frequency adjustment

Calibration of the TSR-37 has been made extremely simple. There is no need for external frequency difference meters or phase comparators. Just connect a 5 MHz or 10 MHz reference signal from a primary standard (cesium, GPS disciplined rubidium) to the rear panel input. The TSR-37 will automatically sense the signal, evaluate its stability and slowly (typically within 10 minutes) tune the output signals to a frequency accuracy of $< 2 \times 10^{-11}$. The unit will continue to operate with the excellent performance of the internal rubidium oscillator until a new calibration cycle is started. The calibration parameters will be retained in a non-volatile memory.

By connecting the GPS antenna, the TSR-37 can serve as a GPS disciplined frequency standard exceeding even the long-term frequency accuracy of cesium. Automatic frequency adjustment can be disabled with a recessed slide switch. Switch tampering can be prevented by placing a calibration sticker across its access opening.

Functional monitoring/built-in test equipment

Continuous extensive self tests monitor the critical functions of the TSR-37 to ensure its high accuracy. Failures of the equipment hardware compromising the frequency accuracy of the output signals will be detected. When power is applied the unit enters into a warm-up phase for a few minutes until it reaches full accuracy. Front panel LED indicators inform the user about the status of the unit.



MTIE and TDEV





Powersupply

Voltage 100 ... 240 VAC, 50 ... 60 Hz Current consumption max. 1.0 A Power consumption typically 30 W at 230 VAC, 22 W at 110 VAC

Input

1 × external reference signal 5 MHz or 10 MHz sine wave or square wave, 0.5 ... 5.0 Vpp into 50 Ω /BNC, MTIE (200 s) < 1 ns

Unframed outputs

 1×5 MHz sine wave, 1 Vrms into 50 Ω , BNC 1×10 MHz sine wave, 1 Vrms into 50 Ω , BNC 2 × 2048 kHz, G.703.13 (10/98), 75 Ω unbalanced, BNC 2 × 2048 kHz, G.703.13 (10/98), 120 Ω balanced, BNC Twinax 1×1544 kHz, 2.5 Vpp, 75 Ω unbalanced, BNC 1×1544 kHz, 3 Vpp, 120 Ω balanced, **BNC** Twinax

Framed outputs

1 × 2048 kbps (E1) G.703.9 (10/98), HDB3, 75 Ω unbalanced, BNC 1 × 2048 kbps (E1) G.703.9 (10/98), HDB3, 120 Ω balanced, BNC Twinax 1×1544 kbps (T1) AMI, 75 Ω unbalanced, BNC 1 × 1544 kbps (T1), AMI,

120 Ω balanced, BNC Twinax

Frequency accuracy

Factory shipment: $<5 \times 10^{-11}$ at 25°C With primary reference adjusted: $<2 \times 10^{-11}$ relative to the reference

Internal time base

Rubidium oscillator	
Aging	<5 × 10 ⁻¹¹ /mont
	<1 × 10 ⁻⁹ over 10 year

Physical data

Size	maximum 260 × 120 × 365 mm
	10.24 × 4.72 × 14.37 inch
	$(W \times H \times D, without handle)$
Weight	maximum 4.3 kg

Regulations and standards

EN 61326-1: 1997, EN 61010-1: 1993, CE-mark

Environmental conditions

Humidity 95% non-condensing Temperature +5°C ... +40°C operating with specified accuracy –10°C ... +55°C operating with de-rated accuracy -55°C ... +85°C storage

Specifications TSR-37 GPS only

Input

GPS antenna signal with 5 VDC feeding; N-type connector, female

Frequency accuracy

Factory shipment	<5 × 10 ⁻¹¹ at 25°C		
With primary reference adjusted:			
<2 × 10 ⁻¹¹ I	relative to the reference		
with GPS connected	typically <1 x 10 ⁻¹²		
(AD	EV typically $< 2.5 \times 10^{-12}$)		

GPS engine

12-channel C/A code receiver (L1), tracks up to 12 satellites continuously

Allan deviation (10 MHz sine wave)

t = 1 second	<2.5 × 10 ⁻¹
	typically $<1.0 \times 10^{-1}$
t = 10 seconds	<0.8 × 10 ⁻¹
t = 100 seconds	<0.25 × 10 ⁻¹

Ordering information

DA81700010	TSR-37 Rubidium Timing Signal Reference
DA81700012	TSR-37 GPS Rubidium Timing Signal Reference

Options and accessories

DA83009002	GPS antenna kit, 25 m cable RG58
DA83009003	GPS antenna kit, 50 m cable RG213
DA83009004	GPS antenna kit, 75 m cable RG213
DA83009005	GPS antenna kit, 100 m cable RG213
DA83009006	GPS antenna kit, 150 m cable "low loss"
DA83009007	GPS antenna kit, 200 m cable "low loss"
DA83009025	Lightning protector kit for RG58 cables
DA83009023	Lightning protector kit for RG213 cables
DA83009024	Lightning protector kit for "low loss" cables
DA13116010	Twinax output cable plug
DA81700001	Transport case for TSR-37
DA89990006	Certificate of calibration (when ordered together with a new TSR-37)
DA89990502	Certificate of compliance (COC)

Note: The upgrade to the GPS version can be done only in the factory

All statements, technical information and recommendations related to the products herein are based upon information believed to be reliable or accurate. However, the accuracy or completeness thereof is not guaranteed, and no responsibility is assumed for any inaccuracies. The user assumes all risks and liability whatsoever in connection with the use of a product or its applications. JDSU reserves the right to change at any time without notice the design, specifications, function, fit or form of its products described herein, including withdrawal at any time of a product offered for sale herein. JDSU makes no representations that the products herein are free from any intellectual property claims of others. Please contact JDSU for more information. JDSU and the JDSU logo are trademarks of JDS Uniphase Corporation. Other trademarks are the property of their respective holders. © 2006 JDS Uniphase Corporation. All rights reserved. 30137194 500 0406 TSR37.DS.CPO.TM.AE

Test & Measurement Regional Sales

NORTH AMERICA	LATIN AMERICA	ASIA PACIFIC	EMEA	WEBSITE: www.jdsu.com
TEL: 1 866 228 3762	TEL:+55 11 5503 3800	TEL:+852 2892 0990	TEL:+49 7121 86 2222	-
FAX: +1 301 353 9216	FAX:+55 11 5505 1598	FAX:+852 2892 0770	FAX:+49 7121 86 1222	