

## Tektronix 465, 475, 475A Series Oscilloscopes Specifications

VERTICAL DEFLECTION (2 IDENTICAL CHANNELS)					
Bandwidth* and Rise Time (at all deflection factors from 50 Ω terminated source)		-15° C to +40° C		+40° C to +55° C	
	465	Dc to 100 MHz, 3.5 ns		85 MHz, 4.1 ns	
	475	Dc to 200 MHz, 1.8 ns		175 MHz, 2.0 ns	
	475A	Dc to 250 MHz, 1.4 ns		250 MHz, 1.4 ns	
*Measured at -3 dB, Bandwidth may be limited to approx 20 MHz by bandwidth limit switch.					
Lower -3 dB point, ac coupling 1X probe: 10 Hz or less. 10X probe: 1 Hz or less.					
Deflection Factor at BW		465: 5 mV/div to 5 V/div 475: 2 mV/div to 5 V/div 475A: 5 mV/div to 10 V/div			
1-2-5 sequence, accurate ± 3%. Uncalibrated, continuously variable between steps and to at least 12.5 V/div (465/475) to at least 25 V/div (475A). In cascade mode sensitivity is approx 1 mV/div (465); approx 400 μV/div (475); and approx 2.5 mV/div (475A). Cascaded bandwidth is at least 50 MHz (465/475/475A) when signal out is terminated in 50 Ω.					
Display Modes		Ch 1; Ch 2 (normal and inverted), alternate, chopped (465-approx 250 kHz rate, 475/475A-approx 1 MHz rate), added; X-Y (Ch 1-X, Ch 2-Y)			
CMRR		Common-mode rejection ratio at least 20 dB at 20 MHz (50 MHz for 475/475A) for common-mode signals of 6 div or less			
Automatic Scale Factor		Probe tip deflection factors for 1X or 10X coded probes are automatically indicated by two readout lights behind the knob skirts. All lights are off when the channel is not displayed. Ground reference display selectable at probe (when dc coupled).			
Input R and C		1 MΩ ± 2% paralleled by approx 20 pF.			
Max Input Voltage	Dc Coupled	250 V (dc + peak ac) 500 V (p-p ac at 1 kHz or less)			
	Ac Coupled	500 V (dc + peak ac) 500 V (p-p ac at 1 kHz or less)			
Delay Line		Permits viewing leading edge of displayed waveform			
Probe Power (475/475A only)		Connectors provide correct voltages for two optional P6201 FET Probes			
HORIZONTAL DEFLECTION					
465					
Time Base A		0.05 μs/div to 0.5 s/div (1-2-5 sequence). X10 mag extends max sweep rate to 5 ns/div.			
Time Base B		0.05 μs/div to 50 ms/div (1-2-5 sequence). X10 mag extends max sweep rate to 5 ns/div.			
475/475A					
Time Base A and B		0.01 μs/div to 0.5 s/div (1-2-5 sequence). X10 mag extends max sweep rate to 1 ns/div.			
Variable Time Control		Time Base A (465/475/475A) provides continuously variable uncalibrated sweep rates between steps and to at least 1.25 s/div. Warning light indicates uncalibrated setting.			
Time Base A and B Accuracy, full 10 cm	Unmagnified	+20° C to +30° C		-15° C to +55° C	
		465	475/475A	465	475/475A
	Magnified	± 2%	± 1%	± 3%	± 2%
Horizontal Display Modes		A, mixed sweep, A intensified, B delayed. B ends A for increased intensity in the delayed mode.			
Calibrated Mixed Sweep		Displays A sweep for period determined by delay-time position control, then displays B sweep for remainder of horizontal sweep.			
CALIBRATED SWEEP DELAY					

<b>Delay Time Range</b>		<b>465:</b> 0.2 to X10 delay time/div settings of 200/ns to 0.5 s (minimum delay time is 200 ns). <b>475/475A:</b> 0 to X10 delay time/div settings of 50 ns to 0.5 s (minimum delay time is 50 ns).					
<b>Differential Time Measurement Accuracy</b>		Delay Time Setting		+15° C to 35° C			
		Over one or more major dial divisions		± 1%			
		Less than one major dial division		± 0.01 major dial division			
<b>Jitter</b>		1 part or less in 50,000 (0.002%) of 10X the A sweep time/div setting. 1 part in 20,000 when operating from 50 Hz line.					
<b>TRIGGERING A AND B</b>							
<b>A Trigger Modes</b>		Normal (sweep runs when triggered). Automatic (sweep free-runs in the absence of a triggering signal and for signals below 30 Hz). Single sweep (sweep runs one time on the first triggering event after the reset selector is pressed). Lights indicate when sweep is triggered and when single sweep is ready.					
<b>A Trigger Holdoff</b>		Adjustable control permits a stable presentation of repetitive complex waveforms.					
<b>B Trigger Modes</b>		B runs after delay time (starts automatically at the end of delay time) and B triggerable after delay time (runs when triggered). The B (delayed) sweep runs once, in each of these modes, following the A sweep delay time.					
<b>Time Base A and B Sensitivity and Coupling</b>							
<b>Coupling</b>		<b>465</b>		<b>475</b>		<b>475A</b>	
		To 25 MHz	At 100 MHz	To 40 MHz	At 200 MHz	To 40 MHz	At 250 MHz
<b>DC</b>	<b>Internal</b>	0.3 div deflection	1.5 div deflection	0.3 div deflection	1.5 div deflection	0.3 div deflection	2.0 div deflection
	<b>External</b>	50 mV	150 mV	50 mV	250 mV	50 mV	250 mV
	<b>External +10</b>	500 mV	1.5 V	500 mV	2.5 V	500 mV	2.5 V
<b>Ac</b>		Requirements increase below 60 Hz					
<b>Ac Lf Reject</b>		Requirements increase below 50 kHz					
<b>Ac Hf Reject</b>		Requirements increase below 60 Hz and above 50 kHz					
<b>465 Jitter</b>		0.5 ns or less at 100 MHz and 5 ns/div					
<b>475 Jitter</b>		0.2 ns or less at 200 MHz and 1 ns/div					
<b>475A Jitter</b>		0.2 ns or less at 250 MHz and 1 ns/div					
<b>A Trigger View</b>		A spring-loaded pushbutton overrides other vertical controls and displays the external signal used for A sweep triggering. This provides quick verification of the signal and time comparison between a vertical signal and their trigger signal.					
<b>Level and Slope</b>		Internal, permits selection of triggering at any point on the positive or negative slope of the displayed waveform. Level adjustment through at least ± 2 V in external, through at least ± 20 V in external divided by 10.					
<b>A Sources</b>		Norm, Ch 1, Ch 2, line, external, and external divided by 10					
<b>B Sources</b>		Starts after delay, norm, Ch 1, Ch 2, and external					
<b>External Inputs</b>		R and C approx 1 MΩ paralleled by approx 20 pF. 250 V (dc + peak ac) max input.					
<b>X-Y OPERATION</b>							
<b>465</b>							
<b>Full-sensitivity X-Y (Ch1 Horiz, Ch2 Vert)</b>		5 mV/div to 5 V/div, accurate ± 4%. Bandwidth is dc to at least 4 MHz. Phase difference between amplifiers is 3° or less from dc to 50 kHz.					
<b>475, 475A</b>							
<b>Full-sensitivity X-Y (Ch1</b>		2 mV/div to 5 V/div (475), 5 mV to 10 V/div (475A) accurate ± 3%.					

Horiz, Ch2 Vert)	Bandwidth is dc to at least 3 MHz. Phase difference between amplifiers is 1° or less from dc to 1 MHz.			
DISPLAY				
CRT	8 X 10 cm display. Horizontal and vertical centerlines further marked in 0.2 cm increments. P31 phosphor standard; P11 option. 18 kV accelerating potential.			
Graticule	internal, nonparallax; variable edge lighting; markings for measurement of rise time			
Beam Finder	Compresses trace to within graticule area for ease in determining the location of an offscreen signal. A pre-set intensity level provides a constant brightness.			
Z-Axis Input	Dc coupled, positive-going signal decreases intensity; 5 V p-p signal causes noticeable modulation at normal intensity; dc to 50 MHz.			
ENVIRONMENTAL CAPABILITIES				
Ambient Temperature	Operating: -15° C to +55° C. Nonoperating: -55° C to +75° C. Filtered forced air ventilation is provided.			
Altitude	Operating: to 15,000 ft; max allowable ambient temperature decreased by 1° C/1000 ft from 5000 to 15,000 ft. Nonoperating: to 50,000 ft.			
Vibration	Operating: 15 minutes along each of the three axes, .06 cm (0.025 in) p-p displacement (4 g's at 55 Hz) 10 to 55 to 10 Hz in 1 minute cycles.			
Humidity	Operating and nonoperating: 5 cycles (120 hours) to 95% relative humidity referenced to MIL-E-16400F (par 4.5.9 through 4.5.9.5.1, class 4).			
Shock	Operating and nonoperating: 30 g's 1/2 sine, 11 ms duration, 2 shocks per axis in each direction for a total of 12 shocks.			
OTHER CHARACTERISTICS				
Amplitude Calibrator	Output Voltage	0.3 V	1% 0° C to +40° C	
	Output Current	30 mA	2% +20° C to +30° C	
	Frequency	Approx 1 kHz		
Vertical Signal Output (465)	Ch 1 vertical signal is dc to at least 50 MHz (-3 dB), and approx 25 mV/div terminated into 50 Ω, and approx 50 mV/div terminated into 1 MW. (475/475A) Ch 2 vertical signal is dc to at least 50 MHz (-3 dB), and approx 10 mV/div terminated into 50 Ω, and approx 20 mV/div terminated into 1 MΩ.			
Gate Outputs	Positive gates from both time bases (approx 5 V)			
Power Requirements	Quick-change line voltage selector provides six ranges; 110 V, 115 V, 120 V, 220 V, 230 V, and 240 V, each ± 10%. 48 to 440 Hz, 75 watts (465) or 100 watts (475, 475A) max at 115 V and 60 Hz. Operation from 12 or 24 V dc is available with Option 07.			
Dimensions	Cabinet		Rackmount	
	in	cm	in	cm
Height (w/o pouch)	6.2	15.7	7.0	17.7
Width (with handle)	12.9	32.8	19.0	48.3
Depth (with panel cover)	18.1	46.0	18.0	45.7
Depth (handle extended)	20.3	51.6		
Weights (approx)	lb	kg	lb	kg
Net (without panel cover)	22.8	10.3	29.4	13.3
Net (with panel cover and accessories)	25.3	11.5		
Shipping	37.0	16.7	58.0	26.3