

80A02 EOS/ESD Isolation Module for the DSA8300

Datasheet



The 80A02 EOS/ESD Isolation module protects the sampling bridge of Tektronix DSA8300 ¹ electrical sampling module inputs from damage due to electro-overstress (EOS) and electrostatic discharge (ESD) from circuit boards and cables. The 80A02 is for applications such as electrical TDR circuit board testing and cable testing where large static charges can be stored in the DUT.

Key features

- Single-channel electrostatic discharge (ESD) and electro-overstress (EOS) damage protection for Tektronix DSA8300 electrical sampling modules
- Plugs into and is powered from sampling mainframe
- Compatible with Tektronix extender cables
- <37 ps reflected rise time when used with 80E04 or SD24 electrical sampling TDR modules

Applications

- Electrical sampling module input isolation for high-speed electrical signal analysis
- Circuit-board controlled impedance testing (TDR)

The 80A02

The 80A02 plugs into any available electrical sampling module plug-in slot of the DSA/TDS/CSA8K Series, legacy CSA11K Series, or legacy CSA803 Series sampling oscilloscopes.

The 80A02 provides a front-panel SMA connector to connect the SMA test cable or probe signal from the DUT. The 80A02 passes the acquired DUT signal to a connected electrical sampling module input for measurement after an actuating control (from the matching P80318 or P8018 highperformance probe, or customer-provided external switch, TTL, or CMOS control logic input) signals the 80A02 that the DUT has been grounded to discharge any electrostatic charge remaining in the DUT.

When used with either matching P80318 or P8018 20 GHz handheld probe (with probe tip pressure actuating feature) the 80A02 provides a superior technique and performance capability for electrical sampling module EOS/ ESD protection of acquired electrical signal and TDR measurement. (See P80318 or P8018 product description.)

You can combine the 80A02 with an 80A09 ESD Protection device to further protect sensitive module inputs from voltage spikes that can occur from operator error during highly repetitive tasks. See the 80A09 datasheet for more information (85W-30138-xx). ²

Specifications

Bandwidth >25 GHz

DSA8300 Series, DSA8200 Series, TDS8000 Series, CSA8000 Series, CSA11800 Series, CSA803 Series Applicable mainframes

Connector type SMA female

Manual control input Open circuit for DUT discharging standby state; Closed circuit (<100 kΩ to ground) for measurement

Automated control input Open circuit or logic low (<0.3 V) for DUT discharging; Closed circuit or logic high (>1.0 V) for measurement

Control signal connector Audio stereo phone mini-jack

Switching time, typical 20 ms

Also compatible with DSA8200, TDS/CSA8200, TDS/CSA8000B, and TDS/CSA8000 sampling oscilloscopes.

The 80A09 is not intended for use in applications where long-duration high-voltage spikes occur, such as in PCB manufacturing and cable test. Use the 80A02 EOS/ESD Isolation Module for these conditions (alone or in combination with an 80A09).

Ordering information

Models

80A02 EOS/ESD Isolation Module, single channel

Standard accessories

071-1317-xx 80A02 user manual

015-1022-01 SMA 50 Ω termination cap

174-4878-xx 20 GHz SMA cable, 12 inches

Recommended accessories

174-5230-xx SlotSaver Adapter Extender Cable. Provides power and control to the 80A02 when operated externally from the DSA/TDS/CSA

mainframe, saving slot space (compatible with 80A06³ and 80A02).

Warranty

90 days.





Tektronix is registered to ISO 9001 and ISO 14001 by SRI Quality System Registrar.



Product Area Assessed: The planning, design/development and manufacture of electronic Test and Measurement instruments.

ASEAN / Australasia (65) 6356 3900 Belgium 00800 2255 4835* Central East Europe and the Baltics +41 52 675 3777 Finland +41 52 675 3777 Hong Kong 400 820 5835 Japan 81 (3) 6714 3010 Middle East, Asia, and North Africa +41 52 675 3777 People's Republic of China 400 820 5835 Republic of Korea 001 800 8255 2835 Spain 00800 2255 4835* Taiwan 886 (2) 2722 9622 Austria 00800 2255 4835*
Brazil +55 (11) 3759 7627
Central Europe & Greece +41 52 675 3777
France 00800 2255 4835*
India 000 800 650 1835
Luxembourg +41 52 675 3777
The Netherlands 00800 2255 4835*
Poland +41 52 675 3777
Russia & CIS *7 (195) 6647564
Sweden 00800 2255 4835*

United Kingdom & Ireland 00800 2255 4835*

Balkans, Israel, South Africa and other ISE Countries +41 52 675 3777

Canada 1 800 833 9200 Denmark +45 80 88 1401 Germany 00800 2255 4835* Italy 00800 2255 4835*

Mexico, Central/South America & Caribbean 52 (55) 56 04 50 90

Norway 800 16098 Portugal 80 08 12370 South Africa +41 52 675 3777 Switzerland 00800 2255 4835* USA 1 800 833 9200

* European toll-free number. If not accessible, call: +41 52 675 3777

Updated 10 April 2013

For Further Information. Tektronix maintains a comprehensive, constantly expanding collection of application notes, technical briefs and other resources to help engineers working on the cutting edge of technology. Please visit www.tektronix.com.

Copyright © Tektronix, Inc. All rights reserved. Tektronix products are covered by U.S. and foreign patents, issued and pending. Information in this publication supersedes that in all previously published material. Specification and price change privileges reserved. TEKTRONIX and TEK are registered trademarks of Tektronix, Inc. All other trade names referenced are the service marks, trademarks, or registered trademarks of their respective companies. 26 Jun 2014

85W-16656-6

www.tektronix.com

