

4 GHz Active Probes

P7240 • P6209 Data Sheet



Features & Benefits

- <120 ps Rise Time (Guaranteed)
- 4 GHz Bandwidth
- <0.5 pF Input Capacitance (P6241 Only)
- Small Form Factor Probe Head
- 8 V_{p-p} Dynamic Range (P6241 Only)
- Direct Access to SMDs

- Oscilloscopes Supported:
 - P7240 TDS/CSA7000 Series
 - P6209 CSA/TDS8000, TDS800 Series
- Probe Interfaces:
 - P7240 TekConnect™ Interface
 - P6209 TekProbe SMA Interface

Applications

- High-speed Digital Systems Design
- Component Design/Characterization
- Signal Integrity, Jitter and Timing Analysis
- Manufacturing Engineering and Test
- Signals with Voltage Swings up to 8 V_{p-p}
- Measures 3.0 V Logic, InfiniBand, PCI Express, DDR, Rambus Data Lines, Gigabit Ethernet

Selecting the right probe for your application is key to attaining the best signal fidelity in your measurements. Active probes provide truer signal reproduction and fidelity for high-frequency measurements. Tektronix provides you a wide range of 4 GHz active probes to select from for your application.

Performance You Can Count On

Depend on Tektronix to provide you with performance you can count on. In addition to industry-leading service and support, this product comes backed by a three-year warranty as standard.



TekConnect™ Interface – P7240

The P7240 with TekConnect interface is a high-performance active probe with high bandwidth and low-capacitive loading to make it the probe of choice for demanding design applications, such as Rambus, DDR DRAM and AGP. This probe and others in the family are also suited for applications in the communication industry, for measurements on Fibre Channel and Gigabit Ethernet. With the TekConnect interface, you can be assured that maximum signal integrity is maintained to meet present and future bandwidth needs.

SMA Interface/Sampling Oscilloscopes – P6209

The P6209 provides a high-bandwidth, low circuit loading probing solution for the CSA/TDS8000B sampling oscilloscopes with TekProbe SMA input connection. Based on the P6249 probe design, the P6209 has similar performance and a similar small probe head for access to today's fine-pitch SMDs and connection points.

Characteristics

Model

Characteristic	P7240	P6209
Rise Time	<120 ps	<120 ps
Bandwidth	4.0 GHz	4.0 GHz
Attenuation	5X	5X
DC Resistance	20 kΩ	20 kΩ
Input Capacitance	<1 pF	<1 pF
Dynamic Range	±2 V	±2 V
Offset Range	±5 V	±5 V
Interface	TekConnect™	TekProbe SMA

Ordering Information

P7240

4.0 GHz Active Probe.

P6209

4.0 GHz Active Probe.

Warranty – Three years.

User Manuals –

P7240: Order 071-0759-xx.

P6209: Order 071-0634-xx.

Included Accessories

Product Name/Description	Part Number	Quantity
Customizable Ground Lead (Set of 5)	196-3482-00	1
Lead Set: 196343700 (3) 196345700 (2)	196-3456-00	1
Adapter Spring (Set of 10)	016-1774-00	1
SMT KlipChip™ Adapter	206-0364-01	2
Pogo Pin (Set of 10)	016-1772-xx	1
Square Pin Socket (Set of 10)	016-1773-xx	1
Square Pin Adapter (Set of 4)		
Probe Tip (Set of 30)	131-5638-30	1
Color Coding Bands, 2 Each of 5 Colors	016-1315-00	1
Probe Carrying Case	016-1879-01	1
Accessory Case	016-7164-00	1
Wrist Strap	006-3415-04	1
SureToe™ (Set of 12)	ST501 (Replacement Pkg of 12)	1

Recommended Accessories

Product Name/Description	Part Number	Quantity
SMK4 – IC Grabber (Set of 2)	013-0309-00	1
SureFoot®, 50 mil (Set of 12)	SF501	1
SureFoot, 25 mil (Set of 12)	SF502	1
SureFoot, 0.5 mil (Set of 12)	SF503	1

Support Options

Opt. C3 – Calibration Service 3 Years.

Opt. C5 – Calibration Service 5 Years.

Opt. D1 – Calibration Data Report.

Opt. D3 – Calibration Data Report 3 Years (with Opt. C3).

Opt. D5 – Calibration Data Report 5 Years (with Opt. C5).

Opt. R5 – Repair Service 5 Years.