



TIMCO INSTRUMENTS, LLC

Impulse Phaser

Cable Identification System

and

Cable Phasing System

Cat. No. 541001-10; -20; -30

Specifications:

Transmitter:

Output Voltage: 95-100 V.D.C. (nominal)

Output Power: 5 joules @ 10 Amps
(nominal)

Output Pulse Rate: 30-36 pulses per
minute

Power Source: 120 volts A.C. @ 60 Hz.
or
12v sealed battery

Controls: Red A.C. Indicator
On/Off toggle switch
Red and amber indicator lamps

Connections: 9' A.C. cord for A.C.
operation;
8' Red & Yellow output hookup
cables.

Weight & Dimensions: 15 lbs.
16" x 7 1/2" x 7"

Total Weight: 17 lbs. with all
components
stored in the transmitter
case and tray.

Detector:

Power Source: 9v Alkaline transistor battery

Controls: Momentary contact "ON" switch
Meter zero control knob
Signal sensitivity control knob

Connections: 4 Pin microphone jack

Weight & Dimensions: 1 lb.
5 3/4" x 3 5/8" x 1 3/4"

Accessories Included:

48" adjustable neck strap for the detector

One clamp-on, as ordered, either 1 1/4", 2 1/8" or 5"
opening

[Impulse Phaser Home Page](#)

[Timco Instrument's Home Page](#)

Visitor Counter

